

Amazon

Exam Questions AWS-Certified-DevOps-Engineer-Professional

Amazon AWS Certified DevOps Engineer Professional



NEW QUESTION 1

A company runs an application on one Amazon EC2 instance. Application metadata is stored in Amazon S3 and must be retrieved if the instance is restarted. The instance must restart or relaunch automatically if the instance becomes unresponsive.

Which solution will meet these requirements?

- A. Create an Amazon CloudWatch alarm for the StatusCheckFailed metri
- B. Use the recover action to stop and start the instanc
- C. Use an S3 event notification to push the metadata to the instance when the instance is back up and running.
- D. Configure AWS OpsWorks, and use the auto healing feature to stop and start the instanc
- E. Use a lifecycle event in OpsWorks to pull the metadata from Amazon S3 and update it on the instance.
- F. Use EC2 Auto Recovery to automatically stop and start the instance in case of a failur
- G. Use an S3 event notification to push the metadata to the instance when the instance is back up and running.
- H. Use AWS CloudFormation to create an EC2 instance that includes the UserData property for the EC2 resourc
- I. Add a command in UserData to retrieve the application metadata from Amazon S3.

Answer: B

Explanation:

<https://aws.amazon.com/blogs/mt/how-to-set-up-aws-opsworks-stacks-auto-healing-notifications-in-amazon-cloudwatch-events/>

NEW QUESTION 2

A company has an application that runs on AWS Lambda and sends logs to Amazon CloudWatch Logs. An Amazon Kinesis data stream is subscribed to the log groups in CloudWatch Logs. A single consumer Lambda function processes the logs from the data stream and stores the logs in an Amazon S3 bucket.

The company's DevOps team has noticed high latency during the processing and ingestion of some logs.

Which combination of steps will reduce the latency? (Select THREE.)

- A. Create a data stream consumer with enhanced fan-ou
- B. Set the Lambda function that processes the logs as the consumer.
- C. Increase the ParallelizationFactor setting in the Lambda event source mapping.
- D. Configure reserved concurrency for the Lambda function that processes the logs.
- E. Increase the batch size in the Kinesis data stream.
- F. Turn off the ReportBatchItemFailures setting in the Lambda event source mapping.
- G. Increase the number of shards in the Kinesis data stream.

Answer: ABC

Explanation:

The latency in processing and ingesting logs can be caused by several factors, such as the throughput of the Kinesis data stream, the concurrency of the Lambda function, and the configuration of the event source mapping. To reduce the latency, the following steps can be taken:

? Create a data stream consumer with enhanced fan-out. Set the Lambda function that processes the logs as the consumer. This will allow the Lambda function to receive records from the data stream with dedicated throughput of up to 2 MB per second per shard, independent of other consumers¹. This will reduce the contention and delay in accessing the data stream.

? Increase the ParallelizationFactor setting in the Lambda event source mapping. This will allow the Lambda service to invoke more instances of the function concurrently to process the records from the data stream². This will increase the processing capacity and reduce the backlog of records in the data stream.

? Configure reserved concurrency for the Lambda function that processes the logs. This will ensure that the function has enough concurrency available to handle the increased load from the data stream³. This will prevent the function from being throttled by the account-level concurrency limit.

The other options are not effective or may have negative impacts on the latency. Option D is not suitable because increasing the batch size in the Kinesis data stream will increase the amount of data that the Lambda function has to process in each invocation, which may increase the execution time and latency⁴. Option E is not advisable because turning off the ReportBatchItemFailures setting in the Lambda event source mapping will prevent the Lambda service from retrying the failed records, which may result in data loss. Option F is not necessary because increasing the number of shards in the Kinesis data stream will increase the throughput of the data stream, but it will not affect the processing speed of the Lambda function, which is the bottleneck in this scenario.

References:

? 1: Using AWS Lambda with Amazon Kinesis Data Streams - AWS Lambda

? 2: AWS Lambda event source mappings - AWS Lambda

? 3: Managing concurrency for a Lambda function - AWS Lambda

? 4: AWS Lambda function scaling - AWS Lambda

? : AWS Lambda event source mappings - AWS Lambda

? : Scaling Amazon Kinesis Data Streams with AWS CloudFormation - Amazon Kinesis Data Streams

NEW QUESTION 3

A company deploys a web application on Amazon EC2 instances that are behind an Application Load Balancer (ALB). The company stores the application code in an AWS CodeCommit repository. When code is merged to the main branch, an AWS Lambda function invokes an AWS CodeBuild project. The CodeBuild project packages the code, stores the packaged code in AWS CodeArtifact, and invokes AWS Systems Manager Run Command to deploy the packaged code to the EC2 instances.

Previous deployments have resulted in defects, EC2 instances that are not running the latest version of the packaged code, and inconsistencies between instances.

Which combination of actions should a DevOps engineer take to implement a more reliable deployment solution? (Select TWO.)

- A. Create a pipeline in AWS CodePipeline that uses the CodeCommit repository as a source provide
- B. Configure pipeline stages that run the CodeBuild project in parallel to build and test the applicatio
- C. In the pipeline, pass the CodeBuild project output artifact to an AWS CodeDeploy action.
- D. Create a pipeline in AWS CodePipeline that uses the CodeCommit repository as a source provide
- E. Create separate pipeline stages that run a CodeBuild project to build and then test the applicatio
- F. In the pipeline, pass the CodeBuild project output artifact to an AWS CodeDeploy action.
- G. Create an AWS CodeDeploy application and a deployment group to deploy the packaged code to the EC2 instance
- H. Configure the ALB for the deployment group.
- I. Create individual Lambda functions that use AWS CodeDeploy instead of Systems Manager to run build, test, and deploy actions.
- J. Create an Amazon S3 bucke
- K. Modify the CodeBuild project to store the packages in the S3 bucket instead of in CodeArtifac

L. Use deploy actions in CodeDeploy to deploy the artifact to the EC2 instances.

Answer: AC

Explanation:

To implement a more reliable deployment solution, a DevOps engineer should take the following actions:

? Create a pipeline in AWS CodePipeline that uses the CodeCommit repository as a source provider. Configure pipeline stages that run the CodeBuild project in parallel to build and test the application. In the pipeline, pass the CodeBuild project output artifact to an AWS CodeDeploy action. This action will improve the deployment reliability by automating the entire process from code commit to deployment, reducing human errors and inconsistencies. By running the build and test stages in parallel, the pipeline can also speed up the delivery time and provide faster feedback. By using CodeDeploy as the deployment action, the pipeline can leverage the features of CodeDeploy, such as traffic shifting, health checks, rollback, and deployment configuration¹²³

? Create an AWS CodeDeploy application and a deployment group to deploy the packaged code to the EC2 instances. Configure the ALB for the deployment group. This action will improve the deployment reliability by using CodeDeploy to orchestrate the deployment across multiple EC2 instances behind an ALB. CodeDeploy can perform blue/green deployments or in-place deployments with traffic shifting, which can minimize downtime and reduce risks. CodeDeploy can also monitor the health of the instances during and after the deployment, and automatically roll back if any issues are detected. By configuring the ALB for the deployment group, CodeDeploy can register and deregister instances from the load balancer as needed, ensuring that only healthy instances receive traffic⁴⁵

The other options are not correct because they do not improve the deployment reliability or follow best practices. Creating separate pipeline stages that run a CodeBuild project to build and then test the application is not a good option because it will increase the pipeline execution time and delay the feedback loop.

Creating individual Lambda functions that use CodeDeploy instead of Systems Manager to run build, test, and deploy actions is not a valid option because it will add unnecessary complexity and cost to the solution. Lambda functions are not designed for long-running tasks such as building or deploying applications.

Creating an Amazon S3 bucket and modifying the CodeBuild project to store the packages in the S3 bucket instead of in CodeArtifact is not a necessary option because it will not affect the deployment reliability. CodeArtifact is a secure, scalable, and cost-effective package management service that can store and share software packages for application development⁶⁷

References:

? 1: What is AWS CodePipeline? - AWS CodePipeline

? 2: Create a pipeline in AWS CodePipeline - AWS CodePipeline

? 3: Deploy an application with AWS CodeDeploy - AWS CodePipeline

? 4: What is AWS CodeDeploy? - AWS CodeDeploy

? 5: Configure an Application Load Balancer for your blue/green deployments - AWS CodeDeploy

? 6: What is AWS Lambda? - AWS Lambda

? 7: What is AWS CodeArtifact? - AWS CodeArtifact

NEW QUESTION 4

A company uses Amazon S3 to store proprietary information. The development team creates buckets for new projects on a daily basis. The security team wants to ensure that all existing and future buckets have encryption logging and versioning enabled. Additionally, no buckets should ever be publicly read or write accessible.

What should a DevOps engineer do to meet these requirements?

- A. Enable AWS CloudTrail and configure automatic remediation using AWS Lambda.
- B. Enable AWS Config rules and configure automatic remediation using AWS Systems Manager documents.
- C. Enable AWS Trusted Advisor and configure automatic remediation using Amazon EventBridge.
- D. Enable AWS Systems Manager and configure automatic remediation using Systems Manager documents.

Answer: B

Explanation:

<https://aws.amazon.com/blogs/mt/aws-config-auto-remediation-s3-compliance/> <https://aws.amazon.com/blogs/aws/aws-config-rules-dynamic-compliance-checking-for-cloud-resources/>

NEW QUESTION 5

A company has an AWS CodePipeline pipeline that is configured with an Amazon S3 bucket in the eu-west-1 Region. The pipeline deploys an AWS Lambda application to the same Region. The pipeline consists of an AWS CodeBuild project build action and an AWS CloudFormation deploy action.

The CodeBuild project uses the aws cloudformation package AWS CLI command to build an artifact that contains the Lambda function code's .zip file and the CloudFormation template. The CloudFormation deploy action references the CloudFormation template from the output artifact of the CodeBuild project's build action.

The company wants to also deploy the Lambda application to the us-east-1 Region by using the pipeline in eu-west-1. A DevOps engineer has already updated the CodeBuild project to use the aws cloudformation package command to produce an additional output artifact for us-east-1.

Which combination of additional steps should the DevOps engineer take to meet these requirements? (Choose two.)

- A. Modify the CloudFormation template to include a parameter for the Lambda function code's zip file location
- B. Create a new CloudFormation deploy action for us-east-1 in the pipeline
- C. Configure the new deploy action to pass in the us-east-1 artifact location as a parameter override.
- D. Create a new CloudFormation deploy action for us-east-1 in the pipeline
- E. Configure the new deploy action to use the CloudFormation template from the us-east-1 output artifact.
- F. Create an S3 bucket in us-east-1. Configure the S3 bucket policy to allow CodePipeline to have read and write access.
- G. Create an S3 bucket in us-east-1. Configure S3 Cross-Region Replication (CRR) from the S3 bucket in eu-west-1 to the S3 bucket in us-east-1.
- H. Modify the pipeline to include the S3 bucket for us-east-1 as an artifact store
- I. Create a new CloudFormation deploy action for us-east-1 in the pipeline
- J. Configure the new deploy action to use the CloudFormation template from the us-east-1 output artifact.

Answer: AB

Explanation:

A. The CloudFormation template should be modified to include a parameter that indicates the location of the .zip file containing the Lambda function's code. This allows the CloudFormation deploy action to use the correct artifact depending on the region. This is critical because Lambda functions need to reference their code artifacts from the same region they are being deployed in. B. You would also need to create a new CloudFormation deploy action for the us-east-1 Region within the pipeline. This action should be configured to use the CloudFormation template from the artifact that was specifically created for us-east-1.

NEW QUESTION 6

A company is developing a new application. The application uses AWS Lambda functions for its compute tier. The company must use a canary deployment for any

changes to the Lambda functions. Automated rollback must occur if any failures are reported. The company's DevOps team needs to create the infrastructure as code (IaC) and the CI/CD pipeline for this solution. Which combination of steps will meet these requirements? (Choose three.)

- A. Create an AWS CloudFormation template for the applicatio
- B. Define each Lambda function in the template by using the AWS::Lambda::Function resource typ
- C. In the template, include a version for the Lambda function by using the AWS::Lambda::Version resource typ
- D. Declare the CodeSha256 property
- E. Configure an AWS::Lambda::Alias resource that references the latest version of the Lambda function.
- F. Create an AWS Serverless Application Model (AWS SAM) template for the applicatio
- G. Define each Lambda function in the template by using the AWS::Serverless::Function resource typ
- H. For each function, include configurations for the AutoPublishAlias property and the DeploymentPreference property
- I. Configure the deployment configuration type to LambdaCanary10Percent10Minutes.
- J. Create an AWS CodeCommit repository
- K. Create an AWS CodePipeline pipeline
- L. Use the CodeCommit repository in a new source stage that starts the pipelin
- M. Create an AWS CodeBuild project to deploy the AWS Serverless Application Model (AWS SAM) templat
- N. Upload the template and source code to the CodeCommit repository
- O. In the CodeCommit repository, create a buildspec.yml file that includes the commands to build and deploy the SAM application.
- P. Create an AWS CodeCommit repository
- Q. Create an AWS CodePipeline pipeline
- R. Use the CodeCommit repository in a new source stage that starts the pipelin
- S. Create an AWS CodeDeploy deployment group that is configured for canary deployments with a DeploymentPreference type of Canary10Percent10Minute
- T. Upload the AWS CloudFormation template and source code to the CodeCommit repository
- . In the CodeCommit repository, create an appspec.yml file that includes the commands to deploy the CloudFormation template.
- . Create an Amazon CloudWatch composite alarm for all the Lambda function
- . Configure an evaluation period and dimensions for Lambd
- . Configure the alarm to enter the ALARM state if any errors are detected or if there is insufficient data.
- . Create an Amazon CloudWatch alarm for each Lambda functio
- . Configure the alarms to enter the ALARM state if any errors are detecte
- . Configure an evaluation period, dimensions for each Lambda function and version, and the namespace as AWS/Lambda on the Errors metric.

Answer: BCF

Explanation:

The requirement is to create the infrastructure as code (IaC) and the CI/CD pipeline for the Lambda application that uses canary deployment and automated rollback. To do this, the DevOps team needs to use the following steps:

? Create an AWS Serverless Application Model (AWS SAM) template for the application. AWS SAM is a framework that simplifies the development and deployment of serverless applications on AWS. AWS SAM allows customers to define Lambda functions and other resources in a template by using a simplified syntax. For each Lambda function, the DevOps team can include configurations for the AutoPublishAlias property and the DeploymentPreference property. The AutoPublishAlias property specifies the name of the alias that points to the latest version of the function. The DeploymentPreference property specifies how CodeDeploy deploys new versions of the function. By configuring the deployment configuration type to LambdaCanary10Percent10Minutes, the DevOps team can enable canary deployment with 10% of traffic shifted to the new version every 10 minutes.

? Create an AWS CodeCommit repository. Create an AWS CodePipeline pipeline.

Use the CodeCommit repository in a new source stage that starts the pipeline. Create an AWS CodeBuild project to deploy the AWS SAM template. CodeCommit is a fully managed source control service that hosts Git repositories. CodePipeline is a fully managed continuous delivery service that automates the release process of software applications. CodeBuild is a fully managed continuous integration service that compiles source code and runs tests. By using these services, the DevOps team can create a CI/CD pipeline for the Lambda application. The pipeline should use the CodeCommit repository as the source stage, where the DevOps team can upload the SAM template and source code. The pipeline should also use a CodeBuild project as the build stage, where the SAM template can be built and deployed.

? Create an Amazon CloudWatch alarm for each Lambda function. Configure the alarms to enter the ALARM state if any errors are detected. Configure an evaluation period, dimensions for each Lambda function and version, and the namespace as AWS/Lambda on the Errors metric. CloudWatch is a service that monitors and collects metrics from AWS resources and applications. CloudWatch alarms are actions that are triggered when a metric crosses a specified threshold. By creating CloudWatch alarms for each Lambda function, the DevOps team can monitor the health and performance of each function version during deployment. By configuring the alarms to enter the ALARM state if any errors are detected, the DevOps team can enable automated rollback if any failures are reported.

NEW QUESTION 7

A company has an application that runs on a fleet of Amazon EC2 instances. The application requires frequent restarts. The application logs contain error messages when a restart is required. The application logs are published to a log group in Amazon CloudWatch Logs.

An Amazon CloudWatch alarm notifies an application engineer through an Amazon Simple Notification Service (Amazon SNS) topic when the logs contain a large number of restart-related error messages. The application engineer manually restarts the application on the instances after the application engineer receives a notification from the SNS topic.

A DevOps engineer needs to implement a solution to automate the application restart on the instances without restarting the instances.

Which solution will meet these requirements in the MOST operationally efficient manner?

- A. Configure an AWS Systems Manager Automation runbook that runs a script to restart the application on the instance
- B. Configure the SNS topic to invoke the runbook.
- C. Create an AWS Lambda function that restarts the application on the instance
- D. Configure the Lambda function as an event destination of the SNS topic.
- E. Configure an AWS Systems Manager Automation runbook that runs a script to restart the application on the instance
- F. Create an AWS Lambda function to invoke the runboo
- G. Configure the Lambda function as an event destination of the SNS topic.
- H. Configure an AWS Systems Manager Automation runbook that runs a script to restart the application on the instance
- I. Configure an Amazon EventBridge rule that reacts when the CloudWatch alarm enters ALARM stat
- J. Specify the runbook as a target of the rule.

Answer: D

Explanation:

This solution meets the requirements in the most operationally efficient manner by automating the application restart process on the instances without restarting them. When the CloudWatch alarm enters the ALARM state, the EventBridge rule is triggered, which in turn invokes the Systems Manager Automation runbook

that contains the script to restart the application on the instances.

NEW QUESTION 8

A company is developing an application that will generate log events. The log events consist of five distinct metrics every one tenth of a second and produce a large amount of data. The company needs to configure the application to write the logs to Amazon Time stream. The company will configure a daily query against the Timestream table.

Which combination of steps will meet these requirements with the FASTEST query performance? (Select THREE.)

- A. Use batch writes to write multiple log events in a Single write operation
- B. Write each log event as a single write operation
- C. Treat each log as a single-measure record
- D. Treat each log as a multi-measure record
- E. Configure the memory store retention period to be longer than the magnetic store retention period
- F. Configure the memory store retention period to be shorter than the magnetic store retention period

Answer: ADF

Explanation:

A comprehensive and detailed explanation is:

? Option A is correct because using batch writes to write multiple log events in a single write operation is a recommended practice for optimizing the performance and cost of data ingestion in Timestream. Batch writes can reduce the number of network round trips and API calls, and can also take advantage of parallel processing by Timestream. Batch writes can also improve the compression ratio of data in the memory store and the magnetic store, which can reduce the storage costs and improve the query performance¹.

? Option B is incorrect because writing each log event as a single write operation is not a recommended practice for optimizing the performance and cost of data ingestion in Timestream. Writing each log event as a single write operation would increase the number of network round trips and API calls, and would also reduce the compression ratio of data in the memory store and the magnetic store. This would increase the storage costs and degrade the query performance¹.

? Option C is incorrect because treating each log as a single-measure record is not a recommended practice for optimizing the query performance in Timestream. Treating each log as a single-measure record would result in creating multiple records for each timestamp, which would increase the storage size and the query latency. Moreover, treating each log as a single-measure record would require using joins to query multiple measures for the same timestamp, which would add complexity and overhead to the query processing².

? Option D is correct because treating each log as a multi-measure record is a recommended practice for optimizing the query performance in Timestream. Treating each log as a multi-measure record would result in creating a single record for each timestamp, which would reduce the storage size and the query latency. Moreover, treating each log as a multi-measure record would allow querying multiple measures for the same timestamp without using joins, which would simplify and speed up the query processing².

? Option E is incorrect because configuring the memory store retention period to be longer than the magnetic store retention period is not a valid option in Timestream. The memory store retention period must always be shorter than or equal to the magnetic store retention period. This ensures that data is moved from the memory store to the magnetic store before it expires out of the memory store³.

? Option F is correct because configuring the memory store retention period to be shorter than the magnetic store retention period is a valid option in Timestream. The memory store retention period determines how long data is kept in the memory store, which is optimized for fast point-in-time queries. The magnetic store retention period determines how long data is kept in the magnetic store, which is optimized for fast analytical queries. By configuring these retention periods appropriately, you can balance your storage costs and query performance according to your application needs³.

References:

? 1: Batch writes

? 2: Multi-measure records vs. single-measure records

? 3: Storage

NEW QUESTION 9

A company requires that its internally facing web application be highly available. The architecture is made up of one Amazon EC2 web server instance and one NAT instance that provides outbound internet access for updates and accessing public data.

Which combination of architecture adjustments should the company implement to achieve high availability? (Choose two.)

- A. Add the NAT instance to an EC2 Auto Scaling group that spans multiple Availability Zone
- B. Update the route tables.
- C. Create additional EC2 instances spanning multiple Availability Zone
- D. Add an Application Load Balancer to split the load between them.
- E. Configure an Application Load Balancer in front of the EC2 instance
- F. Configure Amazon CloudWatch alarms to recover the EC2 instance upon host failure.
- G. Replace the NAT instance with a NAT gateway in each Availability Zone
- H. Update the route tables.
- I. Replace the NAT instance with a NAT gateway that spans multiple Availability Zone
- J. Update the route tables.

Answer: BD

Explanation:

<https://docs.aws.amazon.com/vpc/latest/userguide/vpc-nat-gateway.html>

NEW QUESTION 10

A company detects unusual login attempts in many of its AWS accounts. A DevOps engineer must implement a solution that sends a notification to the company's security team when multiple failed login attempts occur. The DevOps engineer has already created an Amazon Simple Notification Service (Amazon SNS) topic and has subscribed the security team to the SNS topic.

Which solution will provide the notification with the LEAST operational effort?

- A. Configure AWS CloudTrail to send log management events to an Amazon CloudWatch Logs log group
- B. Create a CloudWatch Logs metric filter to match failed ConsoleLogin event
- C. Create a CloudWatch alarm that is based on the metric filter
- D. Configure an alarm action to send messages to the SNS topic.
- E. Configure AWS CloudTrail to send log management events to an Amazon S3 bucket
- F. Create an Amazon Athena query that returns a failure if the query finds failed logins in the logs in the S3 bucket
- G. Create an Amazon EventBridge rule to periodically run the query

- H. Create a second EventBridge rule to detect when the query fails and to send a message to the SNS topic.
- I. Configure AWS CloudTrail to send log data events to an Amazon CloudWatch Logs log group
- J. Create a CloudWatch logs metric filter to match failed ConsoleLogin event
- K. Create a CloudWatch alarm that is based on the metric filter
- L. Configure an alarm action to send messages to the SNS topic.
- M. Configure AWS CloudTrail to send log data events to an Amazon S3 bucket
- N. Configure an Amazon S3 event notification for the s3:ObjectCreated event type
- O. Filter the event type by ConsoleLogin failed event
- P. Configure the event notification to forward to the SNS topic.

Answer: C

Explanation:

The correct answer is C. Configuring AWS CloudTrail to send log data events to an Amazon CloudWatch Logs log group and creating a CloudWatch logs metric filter to match failed ConsoleLogin events is the simplest and most efficient way to monitor and alert on failed login attempts. Creating a CloudWatch alarm that is based on the metric filter and configuring an alarm action to send messages to the SNS topic will ensure that the security team is notified when multiple failed login attempts occur. This solution requires the least operational effort compared to the other options.

Option A is incorrect because it involves configuring AWS CloudTrail to send log management events instead of log data events. Log management events are used to track changes to CloudTrail configuration, such as creating, updating, or deleting a trail. Log data events are used to track API activity in AWS accounts, such as login attempts. Therefore, option A will not capture the failed ConsoleLogin events.

Option B is incorrect because it involves creating an Amazon Athena query and two Amazon EventBridge rules to monitor and alert on failed login attempts. This is a more complex and costly solution than using CloudWatch logs and alarms. Moreover, option B relies on the query returning a failure, which may not happen if the query is executed successfully but does not find any failed logins.

Option D is incorrect because it involves configuring AWS CloudTrail to send log data events to an Amazon S3 bucket and configuring an Amazon S3 event notification for the s3:ObjectCreated event type. This solution will not work because the s3:ObjectCreated event type does not allow filtering by ConsoleLogin failed events. The event notification will be triggered for any object created in the S3 bucket, regardless of the event type. Therefore, option D will generate a lot of false positives and unnecessary notifications. References:

? AWS CloudTrail Log File Examples

? Creating CloudWatch Alarms for CloudTrail Events: Examples

? Monitoring CloudTrail Log Files with Amazon CloudWatch Logs

NEW QUESTION 10

A company wants to ensure that their EC2 instances are secure. They want to be notified if any new vulnerabilities are discovered on their instances and they also want an audit trail of all login activities on the instances.

Which solution will meet these requirements?

- A. Use AWS Systems Manager to detect vulnerabilities on the EC2 instances Install the Amazon Kinesis Agent to capture system logs and deliver them to Amazon S3.
- B. Use AWS Systems Manager to detect vulnerabilities on the EC2 instances Install the Systems Manager Agent to capture system logs and view login activity in the CloudTrail console.
- C. Configure Amazon CloudWatch to detect vulnerabilities on the EC2 instances Install the AWS Config daemon to capture system logs and view them in the AWS Config console.
- D. Configure Amazon Inspector to detect vulnerabilities on the EC2 instances Install the Amazon CloudWatch Agent to capture system logs and record them via Amazon CloudWatch Logs.

Answer: D

Explanation:

This solution will meet the requirements because it will use Amazon Inspector to scan the EC2 instances for any new vulnerabilities and generate findings that can be viewed in the Inspector console or sent as notifications via Amazon Simple Notification Service (SNS). It will also use the Amazon CloudWatch Agent to collect and send system logs from the EC2 instances to Amazon CloudWatch Logs, where they can be stored, searched, and analyzed. The system logs can provide an audit trail of all login activities on the instances, as well as other useful information such as performance metrics, errors, and events.

<https://docs.aws.amazon.com/inspector/latest/user/what-is-inspector.html>

NEW QUESTION 14

A company uses an organization in AWS Organizations to manage its AWS accounts. The company recently acquired another company that has standalone AWS accounts. The acquiring company's DevOps team needs to consolidate the administration of the AWS accounts for both companies and retain full administrative control of the accounts. The DevOps team also needs to collect and group findings across all the accounts to implement and maintain a security posture.

Which combination of steps should the DevOps team take to meet these requirements? (Select TWO.)

- A. Invite the acquired company's AWS accounts to join the organization
- B. Create an SCP that has full administrative privilege
- C. Attach the SCP to the management account.
- D. Invite the acquired company's AWS accounts to join the organization
- E. Create the OrganizationAccountAccessRole IAM role in the invited account
- F. Grant permission to the management account to assume the role.
- G. Use AWS Security Hub to collect and group findings across all accounts
- H. Use Security Hub to automatically detect new accounts as the accounts are added to the organization.
- I. Use AWS Firewall Manager to collect and group findings across all accounts
- J. Enable all features for the organization
- K. Designate an account in the organization as the delegated administrator account for Firewall Manager.
- L. Use Amazon Inspector to collect and group findings across all accounts
- M. Designate an account in the organization as the delegated administrator account for Amazon Inspector.

Answer: BC

Explanation:

The correct answer is B and C. Option B is correct because inviting the acquired company's AWS accounts to join the organization and creating the OrganizationAccountAccessRole IAM role in the invited accounts allows the management account to assume the role and gain full administrative access to the member accounts. Option C is correct because using AWS Security Hub to collect and group findings across all accounts enables the DevOps team to monitor and improve the security posture of the organization. Security Hub can automatically detect new accounts as the accounts are added to the organization and

enable Security Hub for them. Option A is incorrect because creating an SCP that has full administrative privileges and attaching it to the management account does not grant the management account access to the member accounts. SCPs are used to restrict the permissions of the member accounts, not to grant permissions to the management account. Option D is incorrect because using AWS Firewall Manager to collect and group findings across all accounts is not a valid use case for Firewall Manager. Firewall Manager is used to centrally configure and manage firewall rules across the organization, not to collect and group security findings. Option E is incorrect because using Amazon Inspector to collect and group findings across all accounts is not a valid use case for Amazon Inspector. Amazon Inspector is used to assess the security and compliance of applications running on Amazon EC2 instances, not to collect and group security findings across accounts. References:

- ? Inviting an AWS account to join your organization
- ? Enabling and disabling AWS Security Hub
- ? Service control policies
- ? AWS Firewall Manager
- ? Amazon Inspector

NEW QUESTION 17

A company's DevOps engineer is working in a multi-account environment. The company uses AWS Transit Gateway to route all outbound traffic through a network operations account. In the network operations account all account traffic passes through a firewall appliance for inspection before the traffic goes to an internet gateway.

The firewall appliance sends logs to Amazon CloudWatch Logs and includes event severities of CRITICAL, HIGH, MEDIUM, LOW, and INFO. The security team wants to receive an alert if any CRITICAL events occur. What should the DevOps engineer do to meet these requirements?

- A. Create an Amazon CloudWatch Synthetics canary to monitor the firewall stat
- B. If the firewall reaches a CRITICAL state or logs a CRITICAL event use a CloudWatch alarm to publish a notification to an Amazon Simple Notification Service (Amazon SNS) topic Subscribe the security team's email address to the topic.
- C. Create an Amazon CloudWatch metric filter by using a search for CRITICAL events Publish a custom metric for the findin
- D. Use a CloudWatch alarm based on the custom metric to publish a notification to an Amazon Simple Notification Service (Amazon SNS) topi
- E. Subscribe the security team's email address to the topic.
- F. Enable Amazon GuardDuty in the network operations accoun
- G. Configure GuardDuty to monitor flow logs Create an Amazon EventBridge event rule that is invoked by GuardDuty events that are CRITICAL Define an Amazon Simple Notification Service (Amazon SNS) topic as a target Subscribe the security team's email address to the topic.
- H. Use AWS Firewall Manager to apply consistent policies across all account
- I. Create an Amazo
- J. EventBridge event rule that is invoked by Firewall Manager events that are CRITICAL Define an Amazon Simple Notification Service (Amazon SNS) topic as a target Subscribe the security team's email address to the topic.

Answer: B

Explanation:

"The firewall appliance sends logs to Amazon CloudWatch Logs and includes event severities of CRITICAL, HIGH, MEDIUM, LOW, and INFO"

NEW QUESTION 19

A company uses a series of individual Amazon Cloud Formation templates to deploy its multi-Region Applications. These templates must be deployed in a specific order. The company is making more changes to the templates than previously expected and wants to deploy new templates more efficiently. Additionally, the data engineering team must be notified of all changes to the templates.

What should the company do to accomplish these goals?

- A. Create an AWS Lambda function to deploy the Cloud Formation templates m the required order Use stack policies to alert the data engineering team.
- B. Host the Cloud Formation templates in Amazon S3 Use Amazon S3 events to directly trigger CloudFormation updates and Amazon SNS notifications.
- C. Implement CloudFormation StackSets and use drift detection to trigger update alerts to the data engineering team.
- D. Leverage CloudFormation nested stacks and stack sets (or deployments Use Amazon SNS to notify the data engineering team.

Answer: D

Explanation:

This solution will meet the requirements because it will use CloudFormation nested stacks and stack sets to deploy the templates more efficiently and consistently across multiple regions. Nested stacks allow the company to separate out common components and reuse templates, while stack sets allow the company to create stacks in multiple accounts and regions with a single template. The company can also use Amazon SNS to send notifications to the data engineering team whenever a change is made to the templates or the stacks. Amazon SNS is a service that allows you to publish messages to subscribers, such as email addresses, phone numbers, or other AWS services. By using Amazon SNS, the company can ensure that the data engineering team is aware of all changes to the templates and can take appropriate actions if needed. What is Amazon SNS? - Amazon Simple Notification Service

NEW QUESTION 20

A company has deployed an application in a production VPC in a single AWS account. The application is popular and is experiencing heavy usage. The company's security team wants to add additional security, such as AWS WAF, to the application deployment. However, the application's product manager is concerned about cost and does not want to approve the change unless the security team can prove that additional security is necessary.

The security team believes that some of the application's demand might come from users that have IP addresses that are on a deny list. The security team provides the deny list to a DevOps engineer. If any of the IP addresses on the deny list access the application, the security team wants to receive automated notification in near real time so that the security team can document that the application needs additional security. The DevOps engineer creates a VPC flow log for the production VPC.

Which set of additional steps should the DevOps engineer take to meet these requirements MOST cost-effectively?

- A. Create a log group in Amazon CloudWatch Log
- B. Configure the VPC flow log to capture accepted traffic and to send the data to the log grou
- C. Create an Amazon CloudWatch metric filter for IP addresses on the deny lis
- D. Create a CloudWatch alarm with the metric filter as inpu
- E. Set the period to 5 minutes and the datapoints to alarm to 1. Use an Amazon Simple Notification Service (Amazon SNS) topic to send alarm notices to the security team.
- F. Create an Amazon S3 bucket for log file
- G. Configure the VPC flow log to capture all traffic and to send the data to the S3 bucke
- H. Configure Amazon Athena to return all log files in the S3 bucket for IP addresses on the deny lis

- I. Configure Amazon QuickSight to accept data from Athena and to publish the data as a dashboard that the security team can access
- J. Create a threshold alert of 1 for successful access
- K. Configure the alert to automatically notify the security team as frequently as possible when the alert threshold is met.
- L. Create an Amazon S3 bucket for log files
- M. Configure the VPC flow log to capture accepted traffic and to send the data to the S3 bucket
- N. Configure an Amazon OpenSearch Service cluster and domain for the log files
- O. Create an AWS Lambda function to retrieve the logs from the S3 bucket, format the logs, and load the logs into the OpenSearch Service cluster
- P. Schedule the Lambda function to run every 5 minutes
- Q. Configure an alert and condition in OpenSearch Service to send alerts to the security team through an Amazon Simple Notification Service (Amazon SNS) topic when access from the IP addresses on the deny list is detected.
- R. Create a log group in Amazon CloudWatch Log
- S. Create an Amazon S3 bucket to hold query results
- T. Configure the VPC flow log to capture all traffic and to send the data to the log group
- . Deploy an Amazon Athena CloudWatch connector in AWS Lambda
- . Connect the connector to the log group
- . Configure Athena to periodically query for all accepted traffic from the IP addresses on the deny list and to store the results in the S3 bucket
- . Configure an S3 event notification to automatically notify the security team through an Amazon Simple Notification Service (Amazon SNS) topic when new objects are added to the S3 bucket.

Answer: A

NEW QUESTION 23

A development team uses AWS CodeCommit for version control for applications. The development team uses AWS CodePipeline, AWS CodeBuild, and AWS CodeDeploy for CI/CD infrastructure. In CodeCommit, the development team recently merged pull requests that did not pass long-running tests in the code base. The development team needed to perform rollbacks to branches in the codebase, resulting in lost time and wasted effort.

A DevOps engineer must automate testing of pull requests in CodeCommit to ensure that reviewers more easily see the results of automated tests as part of the pull request review.

What should the DevOps engineer do to meet this requirement?

- A. Create an Amazon EventBridge rule that reacts to the pullRequestStatusChanged event
- B. Create an AWS Lambda function that invokes a CodePipeline pipeline with a CodeBuild action that runs the tests for the application
- C. Program the Lambda function to post the CodeBuild badge as a comment on the pull request so that developers will see the badge in their code review.
- D. Create an Amazon EventBridge rule that reacts to the pullRequestCreated event
- E. Create an AWS Lambda function that invokes a CodePipeline pipeline with a CodeBuild action that runs the tests for the application
- F. Program the Lambda function to post the CodeBuild test results as a comment on the pull request when the test results are complete.
- G. Create an Amazon EventBridge rule that reacts to pullRequestCreated and pullRequestSourceBranchUpdated events
- H. Create an AWS Lambda function that invokes a CodePipeline pipeline with a CodeBuild action that runs the tests for the application
- I. Program the Lambda function to post the CodeBuild badge as a comment on the pull request so that developers will see the badge in their code review.
- J. Create an Amazon EventBridge rule that reacts to the pullRequestStatusChanged event
- K. Create an AWS Lambda function that invokes a CodePipeline pipeline with a CodeBuild action that runs the tests for the application
- L. Program the Lambda function to post the CodeBuild test results as a comment on the pull request when the test results are complete.

Answer: C

Explanation:

<https://aws.amazon.com/es/blogs/devops/complete-ci-cd-with-aws-codecommit-aws-codebuild-aws-codedeploy-and-aws-codepipeline/>

NEW QUESTION 26

A company builds a container image in an AWS CodeBuild project by running Docker commands. After the container image is built, the CodeBuild project uploads the container image to an Amazon S3 bucket. The CodeBuild project has an IAM service role that has permissions to access the S3 bucket.

A DevOps engineer needs to replace the S3 bucket with an Amazon Elastic Container Registry (Amazon ECR) repository to store the container images. The DevOps engineer creates an ECR private image repository in the same AWS Region of the CodeBuild project. The DevOps engineer adjusts the IAM service role with the permissions that are necessary to work with the new ECR repository. The DevOps engineer also places new repository information into the docker build command and the docker push command that are used in the buildspec.yml file.

When the CodeBuild project runs a build job, the job fails when the job tries to access the ECR repository.

Which solution will resolve the issue of failed access to the ECR repository?

- A. Update the buildspec.yml file to log in to the ECR repository by using the aws ecr get-login-password AWS CLI command to obtain an authentication token
- B. Update the docker login command to use the authentication token to access the ECR repository.
- C. Add an environment variable of type SECRETS_MANAGER to the CodeBuild project
- D. In the environment variable, include the ARN of the CodeBuild project's IAM service role
- E. Update the buildspec.yml file to use the new environment variable to log in with the docker login command to access the ECR repository.
- F. Update the ECR repository to be a public image repository
- G. Add an ECR repository policy that allows the IAM service role to have access.
- H. Update the buildspec.yml file to use the AWS CLI to assume the IAM service role for ECR operation
- I. Add an ECR repository policy that allows the IAM service role to have access.

Answer: A

Explanation:

(A) When Docker communicates with an Amazon Elastic Container Registry (ECR) repository, it requires authentication. You can authenticate your Docker client to the Amazon ECR registry with the help of the AWS CLI (Command Line Interface). Specifically, you can use the "aws ecr get-login-password" command to get an authorization token and then use Docker's "docker login" command with that token to authenticate to the registry. You would need to perform these steps in your buildspec.yml file before attempting to push or pull images from/to the ECR repository.

NEW QUESTION 29

A DevOps engineer is planning to deploy a Ruby-based application to production. The application needs to interact with an Amazon RDS for MySQL database and should have automatic scaling and high availability. The stored data in the database is critical and should persist regardless of the state of the application stack. The DevOps engineer needs to set up an automated deployment strategy for the application with automatic rollbacks. The solution also must alert the application

team when a deployment fails.

Which combination of steps will meet these requirements? (Select THREE.)

- A. Deploy the application on AWS Elastic Beanstalk
- B. Deploy an Amazon RDS for MySQL DB instance as part of the Elastic Beanstalk configuration.
- C. Deploy the application on AWS Elastic Beanstalk
- D. Deploy a separate Amazon RDS for MySQL DB instance outside of Elastic Beanstalk.
- E. Configure a notification email address that alerts the application team in the AWS Elastic Beanstalk configuration.
- F. Configure an Amazon EventBridge rule to monitor AWS Health event
- G. Use an Amazon Simple Notification Service (Amazon SNS) topic as a target to alert the application team.
- H. Use the immutable deployment method to deploy new application versions.
- I. Use the rolling deployment method to deploy new application versions.

Answer: BDE

Explanation:

For deploying a Ruby-based application with requirements for interaction with an Amazon RDS for MySQL database, automatic scaling, high availability, and data persistence, the following steps will meet the requirements:

? B. Deploy the application on AWS Elastic Beanstalk. Deploy a separate Amazon RDS for MySQL DB instance outside of Elastic Beanstalk. This approach ensures that the database persists independently of the Elastic Beanstalk environment, which can be torn down and recreated without affecting the database¹²³.

? E. Use the immutable deployment method to deploy new application versions. Immutable deployments provide a zero-downtime deployment method that ensures that if any part of the deployment process fails, the environment is rolled back to the original state automatically⁴.

? D. Configure an Amazon EventBridge rule to monitor AWS Health events. Use an Amazon Simple Notification Service (Amazon SNS) topic as a target to alert the application team. This setup allows for automated monitoring and alerting of the application team in case of deployment failures or other health events⁵⁶.

References:

? AWS Elastic Beanstalk documentation on deploying Ruby applications¹.

? AWS documentation on application auto-scaling⁷.

? AWS documentation on automated deployment strategies with automatic rollbacks and alerts⁴⁵⁶.

NEW QUESTION 30

A Company uses AWS CodeCommit for source code control. Developers apply their changes to various feature branches and create pull requests to move those changes to the main branch when the changes are ready for production.

The developers should not be able to push changes directly to the main branch. The company applied the AWSCodeCommitPowerUser managed policy to the developers' IAM role, and now these developers can push changes to the main branch directly on every repository in the AWS account.

What should the company do to restrict the developers' ability to push changes to the main branch directly?

- A. Create an additional policy to include a Deny rule for the GitPush and PutFile action
- B. Include a restriction for the specific repositories in the policy statement with a condition that references the main branch.
- A Create an additional policy to include a Deny rule for the GitPush and PutFile actions Include a restriction for the specific repositories in the policy statement with a condition that references the main branch
- C. Remove the IAM policy, and add an AWSCodeCommitReadOnly managed policy
- D. Add an Allow rule for the GitPush and PutFile actions for the specific repositories in the policy statement with a condition that references the main branch.
- E. Modify the IAM policy Include a Deny rule for the GitPush and PutFile actions for the specific repositories in the policy statement with a condition that references the main branch.
- F. Create an additional policy to include an Allow rule for the GitPush and PutFile action
- G. Include a restriction for the specific repositories in the policy statement with a condition that references the feature branches.

Answer: A

Explanation:

By default, the AWSCodeCommitPowerUser managed policy allows users to push changes to any branch in any repository in the AWS account. To restrict the developers' ability to push changes to the main branch directly, an additional policy is needed that explicitly denies these actions for the main branch.

The Deny rule should be included in a policy statement that targets the specific repositories and includes a condition that references the main branch. The policy statement should look something like this:

```
{
  "Effect": "Deny", "Action": [ "codecommit:GitPush", "codecommit:PutFile"
],
  "Resource": "arn:aws:codecommit:<region>:<account-id>:<repository-name>", "Condition": {
    "StringEqualsIfExists": { "codecommit:References": [ "refs/heads/main"
]
}
}
```

NEW QUESTION 34

A company has an on-premises application that is written in Go. A DevOps engineer must move the application to AWS. The company's development team wants to enable blue/green deployments and perform A/B testing.

Which solution will meet these requirements?

- A. Deploy the application on an Amazon EC2 instance, and create an AMI of the instance
- B. Use the AMI to create an automatic scaling launch configuration that is used in an Auto Scaling group
- C. Use Elastic Load Balancing to distribute traffic
- D. When changes are made to the application, a new AMI will be created, which will initiate an EC2 instance refresh.
- E. Use Amazon Lightsail to deploy the application
- F. Store the application in a zipped format in an Amazon S3 bucket
- G. Use this zipped version to deploy new versions of the application to Lightsail
- H. Use Lightsail deployment options to manage the deployment.
- I. Use AWS CodeArtifact to store the application code
- J. Use AWS CodeDeploy to deploy the application to a fleet of Amazon EC2 instances

- K. Use Elastic Load Balancing to distribute the traffic to the EC2 instance
- L. When making changes to the application, upload a new version to CodeArtifact and create a new CodeDeploy deployment.
- M. Use AWS Elastic Beanstalk to host the applicatio
- N. Store a zipped version of the application in Amazon S3. Use that location to deploy new versions of the applicatio
- O. Use Elastic Beanstalk to manage the deployment options.

Answer: D

Explanation:

<https://aws.amazon.com/quickstart/architecture/blue-green-deployment/>

NEW QUESTION 36

An AWS CodePipeline pipeline has implemented a code release process. The pipeline is integrated with AWS CodeDeploy to deploy versions of an application to multiple Amazon EC2 instances for each CodePipeline stage.

During a recent deployment the pipeline failed due to a CodeDeploy issue. The DevOps team wants to improve monitoring and notifications during deployment to decrease resolution times.

What should the DevOps engineer do to create notifications. When issues are discovered?

- A. Implement Amazon CloudWatch Logs for CodePipeline and CodeDeploy create an AWS Config rule to evaluate code deployment issues, and create an Amazon Simple Notification Service (Amazon SNS) topic to notify stakeholders of deployment issues.
- B. Implement Amazon EventBridge for CodePipeline and CodeDeploy create an AWS Lambda function to evaluate code deployment issues, and create an Amazon Simple Notification Service (Amazon SNS) topic to notify stakeholders of deployment issues.
- C. Implement AWS CloudTrail to record CodePipeline and CodeDeploy API call information create an AWS Lambda function to evaluate code deployment issues and create an Amazon Simple Notification Service (Amazon SNS) topic to notify stakeholders of deployment issues.
- D. Implement Amazon EventBridge for CodePipeline and CodeDeploy create an Amazo
- E. Inspector assessment target to evaluate code deployment issues and create an Amazon Simpl
- F. Notification Service (Amazon SNS) topic to notify stakeholders of deployment issues.

Answer: B

Explanation:

AWS CloudWatch Events can be used to monitor events across different AWS resources, and a CloudWatch Event Rule can be created to trigger an AWS Lambda function when a deployment issue is detected in the pipeline. The Lambda function can then evaluate the issue and send a notification to the appropriate stakeholders through an Amazon SNS topic. This approach allows for real-time notifications and faster resolution times.

NEW QUESTION 41

A company has an application that runs on Amazon EC2 instances that are in an Auto Scaling group. When the application starts up. the application needs to process data from an Amazon S3 bucket before the application can start to serve requests.

The size of the data that is stored in the S3 bucket is growing. When the Auto Scaling group adds new instances, the application now takes several minutes to download and process the data before the application can serve requests. The company must reduce the time that elapses before new EC2 instances are ready to serve requests.

Which solution is the MOST cost-effective way to reduce the application startup time?

- A. Configure a warm pool for the Auto Scaling group with warmed EC2 instances in the Stopped stat
- B. Configure an autoscaling:EC2_INSTANCE_LAUNCHING lifecycle hook on the Auto Scaling grou
- C. Modify the application to complete the lifecycle hook when the application is ready to serve requests.
- D. Increase the maximum instance count of the Auto Scaling grou
- E. Configure an autoscaling:EC2_INSTANCE_LAUNCHING lifecycle hook on the Auto Scaling grou
- F. Modify the application to complete the lifecycle hook when the application is ready to serve requests.
- G. Configure a warm pool for the Auto Scaling group with warmed EC2 instances in the Running stat
- H. Configure an autoscaling:EC2_INSTANCE_LAUNCHING lifecycle hook on the Auto Scaling grou
- I. Modify the application to complete the lifecycle hook when the application is ready to serve requests.
- J. Increase the maximum instance count of the Auto Scaling grou
- K. Configure an autoscaling:EC2_INSTANCE_LAUNCHING lifecycle hook on the Auto Scaling grou
- L. Modify the application to complete the lifecycle hook and to place the new instance in the Standby state when the application is ready to serve requests.

Answer: A

Explanation:

Option A is the most cost-effective solution. By configuring a warm pool of EC2 instances in the Stopped state, the company can reduce the time it takes for new instances to be ready to serve requests. When the Auto Scaling group launches a new instance, it can attach the stopped EC2 instance from the warm pool. The instance can then be started up immediately, rather than having to wait for the data to be downloaded and processed. This reduces the overall startup time for the application.

NEW QUESTION 43

A company's production environment uses an AWS CodeDeploy blue/green deployment to deploy an application. The deployment includes Amazon EC2 Auto Scaling groups that launch instances that run Amazon Linux 2.

A working appspec. yml file exists in the code repository and contains the following text.

```
version: 0.0
os: linux
files:
  - source: /
    destination: /var/www/html/application
```

A DevOps engineer needs to ensure that a script downloads and installs a license file onto the instances before the replacement instances start to handle request

traffic. The DevOps engineer adds a hooks section to the appspec. yml file.
 Which hook should the DevOps engineer use to run the script that downloads and installs the license file?

- A. AfterBlockTraffic
- B. BeforeBlockTraffic
- C. BeforeInstall
- D. Download Bundle

Answer: C

Explanation:

This hook runs before the new application version is installed on the replacement instances. This is the best place to run the script because it ensures that the license file is downloaded and installed before the replacement instances start to handle request traffic. If you use any other hook, you may encounter errors or inconsistencies in your application.

NEW QUESTION 48

A DevOps engineer is setting up a container-based architecture. The engineer has decided to use AWS CloudFormation to automatically provision an Amazon ECS cluster and an Amazon EC2 Auto Scaling group to launch the EC2 container instances. After successfully creating the CloudFormation stack, the engineer noticed that, even though the ECS cluster and the EC2 instances were created successfully and the stack finished the creation, the EC2 instances were associating with a different cluster.

How should the DevOps engineer update the CloudFormation template to resolve this issue?

- A. Reference the EC2 instances in the AWS: ECS: Cluster resource and reference the ECS cluster in the AWS: ECS: Service resource.
- B. Reference the ECS cluster in the AWS: AutoScaling: LaunchConfiguration resource of the UserData property.
- C. Reference the ECS cluster in the AWS:EC2: Instance resource of the UserData property.
- D. Reference the ECS cluster in the AWS: CloudFormation: CustomResource resource to trigger an AWS Lambda function that registers the EC2 instances with the appropriate ECS cluster.

Answer: B

Explanation:

The UserData property of the AWS: AutoScaling: LaunchConfiguration resource can be used to specify a script that runs when the EC2 instances are launched. This script can include the ECS cluster name as an environment variable for the ECS agent running on the EC2 instances. This way, the EC2 instances will register with the correct ECS cluster. Option A is incorrect because the AWS: ECS: Cluster resource does not have a property to reference the EC2 instances. Option C is incorrect because the EC2 instances are launched by the Auto Scaling group, not by the AWS: EC2: Instance resource. Option D is incorrect because using a custom resource and a Lambda function is unnecessary and overly complex for this scenario. References: AWS::AutoScaling::LaunchConfiguration, Amazon ECS Container Agent Configuration

NEW QUESTION 52

A company plans to use Amazon CloudWatch to monitor its Amazon EC2 instances. The company needs to stop EC2 instances when the average of the NetworkPacketsIn metric is less than 5 for at least 3 hours in a 12-hour time window. The company must evaluate the metric every hour. The EC2 instances must continue to run if there is missing data for the NetworkPacketsIn metric during the evaluation period.

A DevOps engineer creates a CloudWatch alarm for the NetworkPacketsIn metric. The DevOps engineer configures a threshold value of 5 and an evaluation period of 1 hour.

Which set of additional actions should the DevOps engineer take to meet these requirements?

- A. Configure the Datapoints to Alarm value to be 3 out of 12. Configure the alarm to treat missing data as breaching the threshold
- B. Add an AWS Systems Manager action to stop the instance when the alarm enters the ALARM state.
- C. Configure the Datapoints to Alarm value to be 3 out of 12. Configure the alarm to treat missing data as not breaching the threshold
- D. Add an EC2 action to stop the instance when the alarm enters the ALARM state.
- E. Configure the Datapoints to Alarm value to be 9 out of 12. Configure the alarm to treat missing data as breaching the threshold
- F. Add an EC2 action to stop the instance when the alarm enters the ALARM state.
- G. Configure the Datapoints to Alarm value to be 9 out of 12. Configure the alarm to treat missing data as not breaching the threshold
- H. Add an AWS Systems Manager action to stop the instance when the alarm enters the ALARM state.

Answer: B

Explanation:

To meet the requirements, the DevOps engineer needs to configure the CloudWatch alarm to stop the EC2 instances when the average of the NetworkPacketsIn metric is less than 5 for at least 3 hours in a 12-hour time window. This means that the alarm should trigger when 3 out of 12 datapoints are below the threshold of 5. The alarm should also treat missing data as not breaching the threshold, so that the EC2 instances continue to run if there is no data for the metric during the evaluation period. The DevOps engineer can add an EC2 action to stop the instance when the alarm enters the ALARM state, which is a built-in action type for CloudWatch alarms.

NEW QUESTION 53

A company is using an AWS CodeBuild project to build and package an application. The packages are copied to a shared Amazon S3 bucket before being deployed across multiple AWS accounts.

The buildspec.yml file contains the following:

```
version: 0.2
phases:
  build:
    commands:
      - go build -o myapp
  post_build:
    commands:
      - aws s3 cp --acl authenticated-read myapp s3://artifacts/
```

The DevOps engineer has noticed that anybody with an AWS account is able to download the artifacts. What steps should the DevOps engineer take to stop this?

- A. Modify the post_build command to use --acl public-read and configure a bucket policy that grants read access to the relevant AWS accounts only.
- B. Configure a default ACL for the S3 bucket that defines the set of authenticated users as the relevant AWS accounts only and grants read-only access.
- C. Create an S3 bucket policy that grants read access to the relevant AWS accounts and denies read access to the principal “*”.
- D. Modify the post_build command to remove --acl authenticated-read and configure a bucket policy that allows read access to the relevant AWS accounts only.

Answer: D

Explanation:

When setting the flag authenticated-read in the command line, the owner gets FULL_CONTROL. The AuthenticatedUsers group (Anyone with an AWS account) gets READ access. Reference: <https://docs.aws.amazon.com/AmazonS3/latest/userguide/acl-overview.html>

NEW QUESTION 58

A company is using AWS CodePipeline to automate its release pipeline. AWS CodeDeploy is being used in the pipeline to deploy an application to Amazon Elastic Container Service (Amazon ECS) using the blue/green deployment model. The company wants to implement scripts to test the green version of the application before shifting traffic. These scripts will complete in 5 minutes or less. If errors are discovered during these tests, the application must be rolled back. Which strategy will meet these requirements?

- A. Add a stage to the CodePipeline pipeline between the source and deploy stage
- B. Use AWS CodeBuild to create a runtime environment and build commands in the buildspec file to invoke test script
- C. If errors are found, use the aws deploy stop-deployment command to stop the deployment.
- D. Add a stage to the CodePipeline pipeline between the source and deploy stage
- E. Use this stage to invoke an AWS Lambda function that will run the test script
- F. If errors are found, use the aws deploy stop-deployment command to stop the deployment.
- G. Add a hooks section to the CodeDeploy AppSpec file
- H. Use the AfterAllowTestTraffic lifecycle event to invoke an AWS Lambda function to run the test script
- I. If errors are found, exit the Lambda function with an error to initiate rollback.
- J. Add a hooks section to the CodeDeploy AppSpec file
- K. Use the AfterAllowTraffic lifecycle event to invoke the test script
- L. If errors are found, use the aws deploy stop-deployment CLI command to stop the deployment.

Answer: C

Explanation:

<https://docs.aws.amazon.com/codedeploy/latest/userguide/reference-appspec-file-structure-hooks.html>

NEW QUESTION 60

A company is implementing an Amazon Elastic Container Service (Amazon ECS) cluster to run its workload. The company architecture will run multiple ECS services on the cluster. The architecture includes an Application Load Balancer on the front end and uses multiple target groups to route traffic. A DevOps engineer must collect application and access logs. The DevOps engineer then needs to send the logs to an Amazon S3 bucket for near-real-time analysis.

Which combination of steps must the DevOps engineer take to meet these requirements? (Choose three.)

- A. Download the Amazon CloudWatch Logs container instance from AW
- B. Configure this instance as a tas
- C. Update the application service definitions to include the logging task.
- D. Install the Amazon CloudWatch Logs agent on the ECS instance
- E. Change the logging driver in the ECS task definition to awslogs.
- F. Use Amazon EventBridge to schedule an AWS Lambda function that will run every 60 seconds and will run the Amazon CloudWatch Logs create-export-task command
- G. Then point the output to the logging S3 bucket.
- H. Activate access logging on the AL
- I. Then point the ALB directly to the logging S3 bucket.
- J. Activate access logging on the target groups that the ECS services use
- K. Then send the logs directly to the logging S3 bucket.
- L. Create an Amazon Kinesis Data Firehose delivery stream that has a destination of the logging S3 bucket
- M. Then create an Amazon CloudWatch Logs subscription filter for Kinesis Data Firehose.

Answer: BDF

Explanation:

<https://docs.aws.amazon.com/AmazonECS/latest/developerguide/ecs-logging-monitoring.html>

NEW QUESTION 65

A company uses AWS Directory Service for Microsoft Active Directory as its identity provider (IdP). The company requires all infrastructure to be defined and deployed by AWS CloudFormation.

A DevOps engineer needs to create a fleet of Windows-based Amazon EC2 instances to host an application. The DevOps engineer has created a CloudFormation template that contains an EC2 launch template, IAM role, EC2 security group, and EC2 Auto Scaling group. The DevOps engineer must implement a solution that joins all EC2 instances to the domain of the AWS Managed Microsoft AD directory.

Which solution will meet these requirements with the MOST operational efficiency?

- A. In the CloudFormation template, create an AWS::SSM::Document resource that joins the EC2 instance to the AWS Managed Microsoft AD domain by using the parameters for the existing director
- B. Update the launch template to include the SSMAssociation property to use the new SSM document
- C. Attach the AmazonSSMManagedInstanceCore and AmazonSSMDirectoryServiceAccess AWS managed policies to the IAM role that the EC2 instances use.
- D. In the CloudFormation template, update the launch template to include specific tags that propagate on launch
- E. Create an AWS::SSM::Association resource to associate the AWS- JoinDirectoryServiceDomain Automation runbook with the EC2 instances that have the specified tag

- F. Define the required parameters to join the AWS Managed Microsoft AD director
- G. Attach the AmazonSSMManagedInstanceCore and AmazonSSMDirectoryServiceAccess AWS managed policies to the IAM role that the EC2 instances use.
- H. Store the existing AWS Managed Microsoft AD domain connection details in AWS Secrets Manager
- I. In the CloudFormation template, create an AWS::SSM::Association resource to associate the AWS-CreateManagedWindowsInstanceWithApproval Automation runbook with the EC2 Auto Scaling group
- J. Pass the ARNs for the parameters from Secrets Manager to join the domain
- K. Attach the AmazonSSMDirectoryServiceAccess and SecretsManagerReadWrite AWS managed policies to the IAM role that the EC2 instances use.
- L. Store the existing AWS Managed Microsoft AD domain administrator credentials in AWS Secrets Manager
- M. In the CloudFormation template, update the EC2 launch template to include user data
- N. Configure the user data to pull the administrator credentials from Secrets Manager and to join the AWS Managed Microsoft AD domain
- O. Attach the AmazonSSMManagedInstanceCore and SecretsManagerReadWrite AWS managed policies to the IAM role that the EC2 instances use.

Answer: B

Explanation:

To meet the requirements, the DevOps engineer needs to create a solution that joins all EC2 instances to the domain of the AWS Managed Microsoft AD directory with the most operational efficiency. The DevOps engineer can use AWS Systems Manager Automation to automate the domain join process using an existing runbook called AWS-JoinDirectoryServiceDomain. This runbook can join Windows instances to an AWS Managed Microsoft AD or Simple AD directory by using PowerShell commands. The DevOps engineer can create an AWS::SSM::Association resource in the CloudFormation template to associate the runbook with the EC2 instances that have specific tags. The tags can be defined in the launch template and propagated on launch to the EC2 instances. The DevOps engineer can also define the required parameters for the runbook, such as the directory ID, directory name, and organizational unit. The DevOps engineer can attach the AmazonSSMManagedInstanceCore and AmazonSSMDirectoryServiceAccess AWS managed policies to the IAM role that the EC2 instances use. These policies grant the necessary permissions for Systems Manager and Directory Service operations.

NEW QUESTION 69

A company manages a web application that runs on Amazon EC2 instances behind an Application Load Balancer (ALB). The EC2 instances run in an Auto Scaling group across multiple Availability Zones. The application uses an Amazon RDS for MySQL DB instance to store the data. The company has configured Amazon Route 53 with an alias record that points to the ALB.

A new company guideline requires a geographically isolated disaster recovery (DR) site with an RTO of 4 hours and an RPO of 15 minutes. Which DR strategy will meet these requirements with the LEAST change to the application stack?

- A. Launch a replica environment of everything except Amazon RDS in a different Availability Zone. Create an RDS read replica in the new Availability Zone and configure the new stack to point to the local RDS DB instance.
- B. Add the new stack to the Route 53 record set by using a health check to configure a failover routing policy.
- C. Launch a replica environment of everything except Amazon RDS in a different AWS Region.
- D. Create an RDS read replica in the new Region and configure the new stack to point to the local RDS DB instance.
- E. Add the new stack to the Route 53 record set by using a health check to configure a latency routing policy.
- F. Launch a replica environment of everything except Amazon RDS in a different AWS Region.
- G. In the event of an outage, copy and restore the latest RDS snapshot from the primary Region to the DR Region.
- H. Adjust the Route 53 record set to point to the ALB in the DR Region.
- I. Launch a replica environment of everything except Amazon RDS in a different AWS Region.
- J. Create an RDS read replica in the new Region and configure the new environment to point to the local RDS DB instance.
- K. Add the new stack to the Route 53 record set by using a health check to configure a failover routing policy.
- L. In the event of an outage, promote the read replica to primary.

Answer: D

NEW QUESTION 70

A company builds an application that uses an Application Load Balancer in front of Amazon EC2 instances that are in an Auto Scaling group. The application is stateless. The Auto Scaling group uses a custom AMI that is fully prebuilt. The EC2 instances do not have a custom bootstrapping process. The AMI that the Auto Scaling group uses was recently deleted. The Auto Scaling group's scaling activities show failures because the AMI ID does not exist. Which combination of steps should a DevOps engineer take to meet these requirements? (Select THREE.)

- A. Create a new launch template that uses the new AMI.
- B. Update the Auto Scaling group to use the new launch template.
- C. Reduce the Auto Scaling group's desired capacity to 0.
- D. Increase the Auto Scaling group's desired capacity by 1.
- E. Create a new AMI from a running EC2 instance in the Auto Scaling group.
- F. Create a new AMI by copying the most recent public AMI of the operating system that the EC2 instances use.

Answer: ABF

Explanation:

To restore the functionality of the Auto Scaling group after the AMI was deleted, the DevOps engineer needs to create a new AMI and update the Auto Scaling group to use it. The DevOps engineer can create a new AMI by copying the most recent public AMI of the operating system that the EC2 instances use. This will ensure that the new AMI has the same operating system as the custom AMI that was deleted. The DevOps engineer can then create a new launch template that uses the new AMI and update the Auto Scaling group to use the new launch template. This will allow the Auto Scaling group to launch new instances with the new AMI.

NEW QUESTION 71

A company's application uses a fleet of Amazon EC2 On-Demand Instances to analyze and process data. The EC2 instances are in an Auto Scaling group. The Auto Scaling group is a target group for an Application Load Balancer (ALB). The application analyzes critical data that cannot tolerate interruption. The application also analyzes noncritical data that can withstand interruption.

The critical data analysis requires quick scalability in response to real-time application demand. The noncritical data analysis involves memory consumption. A DevOps engineer must implement a solution that reduces scale-out latency for the critical data. The solution also must process the noncritical data. Which combination of steps will meet these requirements? (Select TWO.)

- A. For the critical data, modify the existing Auto Scaling group.
- B. Create a warm pool instance in the stopped state.
- C. Define the warm pool size.

- D. Create a new version of the launch template that has detailed monitoring enable
- E. use Spot Instances.
- F. For the critical data, modify the existing Auto Scaling group
- G. Create a warm pool instance in the stopped state
- H. Define the warm pool size
- I. Create a new version of the launch template that has detailed monitoring enable
- J. Use On-Demand Instances.
- K. For the critical data
- L. modify the existing Auto Scaling group
- M. Create a lifecycle hook to ensure that bootstrap scripts are completed successfully
- N. Ensure that the application on the instances is ready to accept traffic before the instances are registered
- O. Create a new version of the launch template that has detailed monitoring enabled.
- P. For the noncritical data, create a second Auto Scaling group that uses a launch template
- Q. Configure the launch template to install the unified Amazon CloudWatch agent and to configure the CloudWatch agent with a custom memory utilization metric
- R. Use Spot Instance
- S. Add the new Auto Scaling group as the target group for the ALB
- T. Modify the application to use two target groups for critical data and noncritical data.
- . For the noncritical data, create a second Auto Scaling group
- . Choose the predefined memory utilization metric type for the target tracking scaling policy
- . Use Spot Instance
- . Add the new Auto Scaling group as the target group for the ALB
- . Modify the application to use two target groups for critical data and noncritical data.

Answer: BD

Explanation:

? For the critical data, using a warm pool¹ can reduce the scale-out latency by having pre-initialized EC2 instances ready to serve the application traffic. Using On-Demand Instances can ensure that the instances are always available and not interrupted by Spot interruptions².

? For the noncritical data, using a second Auto Scaling group with Spot Instances can reduce the cost and leverage the unused capacity of EC2³. Using a launch template with the CloudWatch agent⁴ can enable the collection of memory utilization metrics, which can be used to scale the group based on the memory demand. Adding the second group as a target group for the ALB and modifying the application to use two target groups can enable routing the traffic based on the data type.

References: 1: Warm pools for Amazon EC2 Auto Scaling 2: Amazon EC2 On-Demand Capacity Reservations 3: Amazon EC2 Spot Instances 4: Metrics collected by the CloudWatch agent

NEW QUESTION 73

A business has an application that consists of five independent AWS Lambda functions.

The DevOps engineer has built a CI/CD pipeline using AWS CodePipeline and AWS CodeBuild that builds test packages and deploys each Lambda function in sequence. The pipeline uses an Amazon EventBridge rule to ensure the pipeline starts as quickly as possible after a change is made to the application source code.

After working with the pipeline for a few months the DevOps engineer has noticed the pipeline takes too long to complete.

What should the DevOps engineer implement to BEST improve the speed of the pipeline?

- A. Modify the CodeBuild projects within the pipeline to use a compute type with more available network throughput.
- B. Create a custom CodeBuild execution environment that includes a symmetric multiprocessing configuration to run the builds in parallel.
- C. Modify the CodePipeline configuration to run actions for each Lambda function in parallel by specifying the same run order.
- D. Modify each CodeBuild project to run within a VPC and use dedicated instances to increase throughput.

Answer: C

Explanation:

<https://docs.aws.amazon.com/codepipeline/latest/userguide/reference-pipeline-structure.html>

AWS doc: "To specify parallel actions, use the same integer for each action you want to run in parallel. For example, if you want three actions to run in sequence in a stage, you would give the first action the runOrder value of 1, the second action the runOrder value of 2, and the third the runOrder value of 3. However, if you want the second and third actions to run in parallel, you would give the first action the runOrder value of 1 and both the second and third actions the runOrder value of 2."

NEW QUESTION 78

A company wants to use AWS CloudFormation for infrastructure deployment. The company has strict tagging and resource requirements and wants to limit the deployment to two Regions. Developers will need to deploy multiple versions of the same application.

Which solution ensures resources are deployed in accordance with company policy?

- A. Create AWS Trusted Advisor checks to find and remediate unapproved CloudFormation StackSets.
- B. Create a CloudFormation drift detection operation to find and remediate unapproved CloudFormation StackSets.
- C. Create CloudFormation StackSets with approved CloudFormation templates.
- D. Create AWS Service Catalog products with approved CloudFormation templates.

Answer: D

Explanation:

service catalog uses stacksets and can enforce tag and restrict resources AWS Customer case with tag enforcement

<https://aws.amazon.com/ko/blogs/apn/enforce-centralized-tag-compliance-using-aws-service-catalog-amazon-dynamodb-aws-lambda-and-amazon-cloudwatch-events/> And Youtube video showing how to restrict resources per user with portfolio <https://www.youtube.com/watch?v=LzvhTcqyog>

NEW QUESTION 81

A company uses AWS Organizations to manage multiple accounts. Information security policies require that all unencrypted Amazon EBS volumes be marked as non-compliant. A DevOps engineer needs to automatically deploy the solution and ensure that this compliance check is always present.

Which solution will accomplish this?

- A. Create an AWS CloudFormation template that defines an AWS Inspector rule to check whether EBS encryption is enabled

- B. Save the template to an Amazon S3 bucket that has been shared with all accounts within the company.
- C. Update the account creation script pointing to the CloudFormation template in Amazon S3.
- D. Create an AWS Config organizational rule to check whether EBS encryption is enabled and deploy the rule using the AWS CLI.
- E. Create and apply an SCP to prohibit stopping and deleting AWS Config across the organization.
- F. Create an SCP in Organization.
- G. Set the policy to prevent the launch of Amazon EC2 instances without encryption on the EBS volumes using a conditional expression.
- H. Apply the SCP to all AWS accounts.
- I. Use Amazon Athena to analyze the AWS CloudTrail output, looking for events that deny an ec2: RunInstances action.
- J. Deploy an IAM role to all accounts from a single trusted account.
- K. Build a pipeline with AWS CodePipeline with a stage in AWS Lambda to assume the IAM role, and list all EBS volumes in the account.
- L. Publish a report to Amazon S3.

Answer: B

Explanation:

<https://docs.aws.amazon.com/config/latest/developerguide/ec2-ebs-encryption-by-default.html>

NEW QUESTION 84

A global company manages multiple AWS accounts by using AWS Control Tower. The company hosts internal applications and public applications. Each application team in the company has its own AWS account for application hosting. The accounts are consolidated in an organization in AWS Organizations. One of the AWS Control Tower member accounts serves as a centralized DevOps account with CI/CD pipelines that application teams use to deploy applications to their respective target AWS accounts. An IAM role for deployment exists in the centralized DevOps account.

An application team is attempting to deploy its application to an Amazon Elastic Kubernetes Service (Amazon EKS) cluster in an application AWS account. An IAM role for deployment exists in the application AWS account. The deployment is through an AWS CodeBuild project that is set up in the centralized DevOps account. The CodeBuild project uses an IAM service role for CodeBuild. The deployment is failing with an Unauthorized error during attempts to connect to the cross-account EKS cluster from CodeBuild.

Which solution will resolve this error?

- A. Configure the application account's deployment IAM role to have a trust relationship with the centralized DevOps account.
- B. Configure the trust relationship to allow the sts:AssumeRole action.
- C. Configure the application account's deployment IAM role to have the required access to the EKS cluster.
- D. Configure the EKS cluster aws-auth ConfigMap to map the role to the appropriate system permissions.
- E. Configure the centralized DevOps account's deployment IAM role to have a trust relationship with the application account.
- F. Configure the trust relationship to allow the sts:AssumeRole action.
- G. Configure the centralized DevOps account's deployment IAM role to allow the required access to CodeBuild.
- H. Configure the centralized DevOps account's deployment IAM role to have a trust relationship with the application account.
- I. Configure the trust relationship to allow the sts:AssumeRoleWithSAML action.
- J. Configure the centralized DevOps account's deployment IAM role to allow the required access to CodeBuild.
- K. Configure the application account's deployment IAM role to have a trust relationship with the AWS Control Tower management account.
- L. Configure the trust relationship to allow the sts:AssumeRole action.
- M. Configure the application account's deployment IAM role to have the required access to the EKS cluster.
- N. Configure the EKS cluster aws-auth ConfigMap to map the role to the appropriate system permissions.

Answer: A

Explanation:

In the source AWS account, the IAM role used by the CI/CD pipeline should have permissions to access the source code repository, build artifacts, and any other resources required for the build process. In the destination AWS accounts, the IAM role used for deployment should have permissions to access the AWS resources required for deploying the application, such as EC2 instances, RDS databases, S3 buckets, etc. The exact permissions required will depend on the specific resources being used by the application. The IAM role used for deployment in the destination accounts should also have permissions to assume the IAM role for deployment in the centralized DevOps account. This is typically done using an IAM role trust policy that allows the destination account to assume the DevOps account role.

NEW QUESTION 88

A developer is maintaining a fleet of 50 Amazon EC2 Linux servers. The servers are part of an Amazon EC2 Auto Scaling group, and also use Elastic Load Balancing for load balancing.

Occasionally, some application servers are being terminated after failing ELB HTTP health checks. The developer would like to perform a root cause analysis on the issue, but before being able to access application logs, the server is terminated.

How can log collection be automated?

- A. Use Auto Scaling lifecycle hooks to put instances in a Pending:Wait state.
- B. Create an Amazon CloudWatch alarm for EC2 Instance Terminate Successful and trigger an AWS Lambda function that invokes an SSM Run Command script to collect logs, push them to Amazon S3, and complete the lifecycle action once logs are collected.
- C. Use Auto Scaling lifecycle hooks to put instances in a Terminating:Wait state.
- D. Create an AWS Config rule for EC2 Instance-terminate Lifecycle Action and trigger a step function that invokes a script to collect logs, push them to Amazon S3, and complete the lifecycle action once logs are collected.
- E. Use Auto Scaling lifecycle hooks to put instances in a Terminating:Wait state.
- F. Create an Amazon CloudWatch subscription filter for EC2 Instance Terminate Successful and trigger a CloudWatch agent that invokes a script to collect logs, push them to Amazon S3, and complete the lifecycle action once logs are collected.
- G. Use Auto Scaling lifecycle hooks to put instances in a Terminating:Wait state.
- H. Create an Amazon EventBridge rule for EC2 Instance-terminate Lifecycle Action and trigger an AWS Lambda function that invokes an SSM Run Command script to collect logs, push them to Amazon S3, and complete the lifecycle action once logs are collected.

Answer: D

Explanation:

<https://blog.fourninecloud.com/auto-scaling-lifecycle-hooks-to-export-server-logs-when-instance-terminating-58e06d7c0d6a>

NEW QUESTION 91

A company uses AWS Secrets Manager to store a set of sensitive API keys that an AWS Lambda function uses. When the Lambda function is invoked, the

Lambda function retrieves the API keys and makes an API call to an external service. The Secrets Manager secret is encrypted with the default AWS Key Management Service (AWS KMS) key.

A DevOps engineer needs to update the infrastructure to ensure that only the Lambda function's execution role can access the values in Secrets Manager. The solution must apply the principle of least privilege.

Which combination of steps will meet these requirements? (Select TWO.)

- A. Update the default KMS key for Secrets Manager to allow only the Lambda function's execution role to decrypt.
- B. Create a KMS customer managed key that trusts Secrets Manager and allows the Lambda function's execution role to decrypt
- C. Update Secrets Manager to use the new customer managed key.
- D. Create a KMS customer managed key that trusts Secrets Manager and allows the account's :root principal to decrypt
- E. Update Secrets Manager to use the new customer managed key.
- F. Ensure that the Lambda function's execution role has the KMS permissions scoped on the resource level
- G. Configure the permissions so that the KMS key can encrypt the Secrets Manager secret.
- H. Remove all KMS permissions from the Lambda function's execution role.

Answer: BD

Explanation:

The requirement is to update the infrastructure to ensure that only the Lambda function's execution role can access the values in Secrets Manager. The solution must apply the principle of least privilege, which means granting the minimum permissions necessary to perform a task.

To do this, the DevOps engineer needs to use the following steps:

? Create a KMS customer managed key that trusts Secrets Manager and allows the Lambda function's execution role to decrypt. A customer managed key is a symmetric encryption key that is fully managed by the customer. The customer can define the key policy, which specifies who can use and manage the key. By creating a customer managed key, the DevOps engineer can restrict the decryption permission to only the Lambda function's execution role, and prevent other principals from accessing the secret values. The customer managed key also needs to trust Secrets Manager, which means allowing Secrets Manager to use the key to encrypt and decrypt secrets on behalf of the customer.

? Update Secrets Manager to use the new customer managed key. Secrets Manager allows customers to choose which KMS key to use for encrypting each secret. By default, Secrets Manager uses the default KMS key for Secrets Manager, which is a service-managed key that is shared by all customers in the same AWS Region. By updating Secrets Manager to use the new customer managed key, the DevOps engineer can ensure that only the Lambda function's execution role can decrypt the secret values using that key.

? Ensure that the Lambda function's execution role has the KMS permissions scoped on the resource level. The Lambda function's execution role is an IAM role that grants permissions to the Lambda function to access AWS services and resources. The role needs to have KMS permissions to use the customer managed key for decryption. However, to apply the principle of least privilege, the role should have the permissions scoped on the resource level, which means specifying the ARN of the customer managed key as a condition in the IAM policy statement. This way, the role can only use that specific key and not any other KMS keys in the account.

NEW QUESTION 94

A DevOps engineer is architecting a continuous development strategy for a company's software as a service (SaaS) web application running on AWS. For application and security reasons users subscribing to this application are distributed across multiple. Application Load Balancers (ALBs) each of which has a dedicated Auto Scaling group and fleet of Amazon EC2 instances. The application does not require a build stage and when it is committed to AWS CodeCommit, the application must trigger a simultaneous deployment to all ALBs Auto Scaling groups and EC2 fleets.

Which architecture will meet these requirements with the LEAST amount of configuration?

- A. Create a single AWS CodePipeline pipeline that deploys the application in parallel using unique AWS CodeDeploy applications and deployment groups created for each ALB-Auto Scaling group pair.
- B. Create a single AWS CodePipeline pipeline that deploys the application using a single AWS CodeDeploy application and single deployment group.
- C. Create a single AWS CodePipeline pipeline that deploys the application in parallel using a single AWS CodeDeploy application and unique deployment group for each ALB-Auto Scaling group pair.
- D. Create an AWS CodePipeline pipeline for each ALB-Auto Scaling group pair that deploys the application using an AWS CodeDeploy application and deployment group created for the same ALB-Auto Scaling group pair.

Answer: C

Explanation:

<https://docs.aws.amazon.com/codedeploy/latest/userguide/deployment-groups.html>

NEW QUESTION 96

A company must encrypt all AMIs that the company shares across accounts. A DevOps engineer has access to a source account where an unencrypted custom AMI has been built. The DevOps engineer also has access to a target account where an Amazon EC2 Auto Scaling group will launch EC2 instances from the AMI. The DevOps engineer must share the AMI with the target account.

The company has created an AWS Key Management Service (AWS KMS) key in the source account.

Which additional steps should the DevOps engineer perform to meet the requirements? (Choose three.)

- A. In the source account, copy the unencrypted AMI to an encrypted AMI
- B. Specify the KMS key in the copy action.
- C. In the source account, copy the unencrypted AMI to an encrypted AMI
- D. Specify the default Amazon Elastic Block Store (Amazon EBS) encryption key in the copy action.
- E. In the source account, create a KMS grant that delegates permissions to the Auto Scaling group service-linked role in the target account.
- F. In the source account, modify the key policy to give the target account permissions to create a grant
- G. In the target account, create a KMS grant that delegates permissions to the Auto Scaling group service-linked role.
- H. In the source account, share the unencrypted AMI with the target account.
- I. In the source account, share the encrypted AMI with the target account.

Answer: ADF

Explanation:

The Auto Scaling group service-linked role must have a specific grant in the source account in order to decrypt the encrypted AMI. This is because the service-linked role does not have permissions to assume the default IAM role in the source account. The following steps are required to meet the requirements:

? In the source account, copy the unencrypted AMI to an encrypted AMI. Specify the KMS key in the copy action.

? In the source account, create a KMS grant that delegates permissions to the Auto Scaling group service-linked role in the target account.

? In the source account, share the encrypted AMI with the target account.

? In the target account, attach the KMS grant to the Auto Scaling group service-linked role.

The first three steps are the same as the steps that I described earlier. The fourth step is required to grant the Auto Scaling group service-linked role permissions to decrypt the AMI in the target account.

NEW QUESTION 98

An application running on a set of Amazon EC2 instances in an Auto Scaling group requires a configuration file to operate. The instances are created and maintained with AWS CloudFormation. A DevOps engineer wants the instances to have the latest configuration file when launched and wants changes to the configuration file to be reflected on all the instances with a minimal delay when the CloudFormation template is updated. Company policy requires that application configuration files be maintained along with AWS infrastructure configuration files in source control.

Which solution will accomplish this?

- A. In the CloudFormation template add an AWS Config rule
- B. Place the configuration file content in the rule's InputParameters property and set the Scope property to the EC2 Auto Scaling group
- C. Add an AWS Systems Manager Resource Data Sync resource to the template to poll for updates to the configuration.
- D. In the CloudFormation template add an EC2 launch template resource
- E. Place the configuration file content in the launch template
- F. Configure the cfn-init script to run when the instance is launched and configure the cfn-hup script to poll for updates to the configuration.
- G. In the CloudFormation template add an EC2 launch template resource
- H. Place the configuration file content in the launch template
- I. Add an AWS Systems Manager Resource Data Sync resource to the template to poll for updates to the configuration.
- J. In the CloudFormation template add CloudFormation metadata
- K. Place the configuration file content in the metadata
- L. Configure the cfn-init script to run when the instance is launched and configure the cfn-hup script to poll for updates to the configuration.

Answer: D

Explanation:

Use the AWS::CloudFormation::Init type to include metadata on an Amazon EC2 instance for the cfn-init helper script. If your template calls the cfn-init script, the script looks for resource metadata rooted in the AWS::CloudFormation::Init metadata key. Reference: <https://docs.aws.amazon.com/AWSCloudFormation/latest/UserGuide/aws-resource-init.html>

NEW QUESTION 101

A company wants to use a grid system for a proprietary enterprise in-memory data store on top of AWS. This system can run in multiple server nodes in any Linux-based distribution. The system must be able to reconfigure the entire cluster every time a node is added or removed. When adding or removing nodes an /etc./cluster/nodes config file must be updated listing the IP addresses of the current node members of that cluster.

The company wants to automate the task of adding new nodes to a cluster. What can a DevOps engineer do to meet these requirements?

- A. Use AWS OpsWorks Stacks to layer the server nodes of that cluster
- B. Create a Chef recipe that populates the content of the /etc./cluster/nodes config file and restarts the service by using the current members of the layer
- C. Assign that recipe to the Configure lifecycle event.
- D. Put the file nodes config in version control
- E. Create an AWS CodeDeploy deployment configuration and deployment group based on an Amazon EC2 tag value for the cluster node
- F. When adding a new node to the cluster update the file with all tagged instances and make a commit in version control
- G. Deploy the new file and restart the services.
- H. Create an Amazon S3 bucket and upload a version of the /etc./cluster/nodes config file Create a crontab script that will poll for that S3 file and download it frequently
- I. Use a process manager such as Monit or system, to restart the cluster services when it detects that the new file was modified
- J. When adding a node to the cluster edit the file's most recent members Upload the new file to the S3 bucket.
- K. Create a user data script that lists all members of the current security group of the cluster and automatically updates the /etc/cluster/. nodes config
- L. Trigger whenever a new instance is added to the cluster.

Answer: A

Explanation:

You can run custom recipes manually, but the best approach is usually to have AWS OpsWorks Stacks run them automatically. Every layer has a set of built-in recipes assigned each of five lifecycle events—Setup, Configure, Deploy, Undeploy, and Shutdown. Each time an event occurs for an instance, AWS OpsWorks Stacks runs the associated recipes for each of the instance's layers, which handle the corresponding tasks. For example, when an instance finishes booting, AWS OpsWorks Stacks triggers a Setup event. This event runs the associated layer's Setup recipes, which typically handle tasks such as installing and configuring packages

NEW QUESTION 106

A company manages multiple AWS accounts in AWS Organizations. The company's security policy states that AWS account root user credentials for member accounts must not be used. The company monitors access to the root user credentials.

A recent alert shows that the root user in a member account launched an Amazon EC2 instance. A DevOps engineer must create an SCP at the organization's root level that will prevent the root user in member accounts from making any AWS service API calls.

Which SCP will meet these requirements?

A)

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Effect": "Allow",
      "Action": "*",
      "Resource": "*",
      "Condition": {
        "StringNotLike": { "aws:PrincipalArn": "arn:aws:iam::*:root" }
      }
    }
  ]
}
```

B)

```
"Version": "2012-10-17",
"Statement": [
  {
    "Effect": "Deny",
    "Action": "*",
    "Resource": "*",
    "Principal": { "AWS": "arn:aws:iam::*:root" }
  }
]
```

C)

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Effect": "Deny",
      "Action": "*",
      "Resource": "*",
      "Condition": {
        "StringLike": { "aws:PrincipalArn": "arn:aws:iam::*:root" }
      }
    }
  ]
}
```

D)

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Effect": "Allow",
      "Action": "*",
      "Resource": "*",
      "Principal": "root"
    }
  ]
}
```

- A. Option A
- B. Option B
- C. Option C
- D. Option D

Answer: D

NEW QUESTION 107

A highly regulated company has a policy that DevOps engineers should not log in to their Amazon EC2 instances except in emergencies. If a DevOps engineer does log in the security team must be notified within 15 minutes of the occurrence. Which solution will meet these requirements?

- A. Install the Amazon Inspector agent on each EC2 instance Subscribe to Amazon EventBridge notifications Invoke an AWS Lambda function to check if a message is about user logins If it is send a notification to the security team using Amazon SNS.
- B. Install the Amazon CloudWatch agent on each EC2 instance Configure the agent to push all logs to Amazon CloudWatch Logs and set up a CloudWatch metric filter that searches for user login
- C. If a login is found send a notification to the security team using Amazon SNS.
- D. Set up AWS CloudTrail with Amazon CloudWatch Log
- E. Subscribe CloudWatch Logs to Amazon Kinesis Attach AWS Lambda to Kinesis to parse and determine if a log contains a user login If it does, send a notification to the security team using Amazon SNS.
- F. Set up a script on each Amazon EC2 instance to push all logs to Amazon S3 Set up an S3 event to invoke an AWS Lambda function which invokes an Amazon Athena query to ru
- G. The Athena query checks for logins and sends the output to the security team using Amazon SNS.

Answer: B

Explanation:

<https://aws.amazon.com/blogs/security/how-to-monitor-and-visualize-failed-ssh-access-attempts-to-amazon-ec2-linux-instances/>

NEW QUESTION 112

A company hosts a security auditing application in an AWS account. The auditing application uses an IAM role to access other AWS accounts. All the accounts are in the same organization in AWS Organizations.

A recent security audit revealed that users in the audited AWS accounts could modify or delete the auditing application's IAM role. The company needs to prevent any modification to the auditing application's IAM role by any entity other than a trusted administrator IAM role.

Which solution will meet these requirements?

- A. Create an SCP that includes a Deny statement for changes to the auditing application's IAM rol
- B. Include a condition that allows the trusted administrator IAM role to make change
- C. Attach the SCP to the root of the organization.
- D. Create an SCP that includes an Allow statement for changes to the auditing application's IAM role by the trusted administrator IAM rol
- E. Include a Deny statement for changes by all other IAM principal
- F. Attach the SCP to the IAM service in each AWS account where the auditing application has an IAM role.
- G. Create an IAM permissions boundary that includes a Deny statement for changes to the auditing application's IAM rol
- H. Include a condition that allows the trusted administrator IAM role to make change
- I. Attach the permissions boundary to the audited AWS accounts.
- J. Create an IAM permissions boundary that includes a Deny statement for changes to the auditing application's IAM rol
- K. Include a condition that allows the trusted administrator IAM role to make change
- L. Attach the permissions boundary to the auditing application's IAM role in the AWS accounts.

Answer: A

Explanation:

https://docs.aws.amazon.com/organizations/latest/userguide/orgs_manage_policies_scps.html?icmpid=docs_orgs_console

SCPs (Service Control Policies) are the best way to restrict permissions at the organizational level, which in this case would be used to restrict modifications to the IAM role used by the auditing application, while still allowing trusted administrators to make changes to it. Options C and D are not as effective because IAM permission boundaries are applied to IAM entities (users, groups, and roles), not the account itself, and must be applied to all IAM entities in the account.

NEW QUESTION 115

A DevOps engineer is building a continuous deployment pipeline for a serverless application that uses AWS Lambda functions. The company wants to reduce the customer impact of an unsuccessful deployment. The company also wants to monitor for issues.

Which deploy stage configuration will meet these requirements?

- A. Use an AWS Serverless Application Model (AWS SAM) template to define the serverless applicatio
- B. Use AWS CodeDeploy to deploy the Lambda functions with the Canary10Percent15Minutes Deployment Preference Typ
- C. Use Amazon CloudWatch alarms to monitor the health of the functions.
- D. Use AWS CloudFormation to publish a new stack update, and include Amazon CloudWatch alarms on all resource
- E. Set up an AWS CodePipeline approval action for a developer to verify and approve the AWS CloudFormation change set.
- F. Use AWS CloudFormation to publish a new version on every stack update, and include Amazon CloudWatch alarms on all resource
- G. Use the RoutingConfig property of the AWS::Lambda::Alias resource to update the traffic routing during the stack update.
- H. Use AWS CodeBuild to add sample event payloads for testing to the Lambda function
- I. Publish a new version of the functions, and include Amazon CloudWatch alarm
- J. Update the production alias to point to the new versio
- K. Configure rollbacks to occur when an alarm is in the ALARM state.

Answer: D

Explanation:

Use routing configuration on an alias to send a portion of traffic to a second function version. For example, you can reduce the risk of deploying a new version by configuring the alias to send most of the traffic to the existing version, and only a small percentage of traffic to the new version.

<https://docs.aws.amazon.com/lambda/latest/dg/configuration-aliases.html>

The following are the steps involved in the deploy stage configuration that will meet the requirements:

? Use AWS CodeBuild to add sample event payloads for testing to the Lambda functions.

? Publish a new version of the functions, and include Amazon CloudWatch alarms.

? Update the production alias to point to the new version.

? Configure rollbacks to occur when an alarm is in the ALARM state.

This configuration will help to reduce the customer impact of an unsuccessful deployment

by deploying the new version of the functions to a staging environment first. This will allow the DevOps engineer to test the new version of the functions before

deploying it to production.

The configuration will also help to monitor for issues by including Amazon CloudWatch alarms. These alarms will alert the DevOps engineer if there are any problems with the new version of the functions.

NEW QUESTION 119

A company has a guideline that every Amazon EC2 instance must be launched from an AMI that the company's security team produces. Every month the security team sends an email message with the latest approved AMIs to all the development teams.

The development teams use AWS CloudFormation to deploy their applications. When developers launch a new service they have to search their email for the latest AMIs that the security department sent. A DevOps engineer wants to automate the process that the security team uses to provide the AMI IDs to the development teams.

What is the MOST scalable solution that meets these requirements?

- A. Direct the security team to use CloudFormation to create new versions of the AMIs and to list! the AMI ARNs in an encrypted Amazon S3 object as part of the stack's Outputs Section. Instruct the developers to use a cross-stack reference to load the encrypted S3 object and obtain the most recent AMI ARNs.
- B. Direct the security team to use a CloudFormation stack to create an AWS CodePipeline pipeline that builds new AMIs and places the latest AMI ARNs in an encrypted Amazon S3 object as part of the pipeline output. Instruct the developers to use a cross-stack reference within their own CloudFormation template to obtain the S3 object location and the most recent AMI ARNs.
- C. Direct the security team to use Amazon EC2 Image Builder to create new AMIs and to place the AMI ARNs as parameters in AWS Systems Manager Parameter Store. Instruct the developers to specify a parameter of type SSM in their CloudFormation stack to obtain the most recent AMI ARNs from Parameter Store.
- D. Direct the security team to use Amazon EC2 Image Builder to create new AMIs and to create an Amazon Simple Notification Service (Amazon SNS) topic so that every development team can receive notification.
- E. When the development teams receive a notification, instruct them to write an AWS Lambda function that will update their CloudFormation stack with the most recent AMI ARNs.

Answer: C

Explanation:

<https://docs.aws.amazon.com/AWSCloudFormation/latest/UserGuide/dynamic-references.html>

NEW QUESTION 123

A company wants to deploy a workload on several hundred Amazon EC2 instances. The company will provision the EC2 instances in an Auto Scaling group by using a launch template.

The workload will pull files from an Amazon S3 bucket, process the data, and put the results into a different S3 bucket. The EC2 instances must have least-privilege permissions and must use temporary security credentials.

Which combination of steps will meet these requirements? (Select TWO.)

- A. Create an IAM role that has the appropriate permissions for S3 bucket.
- B. Add the IAM role to an instance profile.
- C. Update the launch template to include the IAM instance profile.
- D. Create an IAM user that has the appropriate permissions for Amazon S3. Generate a secret key and token.
- E. Create a trust anchor and profile.
- F. Attach the IAM role to the profile.
- G. Update the launch template.
- H. Modify the user data to use the new secret key and token.

Answer: AB

Explanation:

To meet the requirements of deploying a workload on several hundred EC2 instances with least-privilege permissions and temporary security credentials, the company should use an IAM role and an instance profile. An IAM role is a way to grant permissions to an entity that you trust, such as an EC2 instance. An instance profile is a container for an IAM role that you can use to pass role information to an EC2 instance when the instance starts. By using an IAM role and an instance profile, the EC2 instances can automatically receive temporary security credentials from the AWS Security Token Service (STS) and use them to access the S3 buckets. This way, the company does not need to manage or rotate any long-term credentials, such as IAM users or access keys.

To use an IAM role and an instance profile, the company should create an IAM role that has the appropriate permissions for S3 buckets. The permissions should allow the EC2 instances to read from the source S3 bucket and write to the destination S3 bucket. The company should also create a trust policy for the IAM role that specifies that EC2 is allowed to assume the role. Then, the company should add the IAM role to an instance profile. An instance profile can have only one IAM role, so the company does not need to create multiple roles or profiles for this scenario.

Next, the company should update the launch template to include the IAM instance profile. A launch template is a way to save launch parameters for EC2 instances, such as the instance type, security group, user data, and IAM instance profile. By using a launch template, the company can ensure that all EC2 instances in the Auto Scaling group have consistent configuration and permissions. The company should specify the name or ARN of the IAM instance profile in the launch template. This way, when the Auto Scaling group launches new EC2 instances based on the launch template, they will automatically receive the IAM role and its permissions through the instance profile.

The other options are not correct because they do not meet the requirements or follow best practices. Creating an IAM user and generating a secret key and token is not a good option because it involves managing long-term credentials that need to be rotated regularly. Moreover, embedding credentials in user data is not secure because user data is visible to anyone who can describe the EC2 instance. Creating a trust anchor and profile is not a valid option because trust anchors are used for certificate-based authentication, not for IAM roles or instance profiles. Modifying user data to use a new secret key and token is also not a good option because it requires updating user data every time the credentials change, which is not scalable or efficient.

References:

- ? 1: [AWS Certified DevOps Engineer - Professional Certification | AWS Certification](#)
- | [AWS](#)
- ? 2: [DevOps Resources - Amazon Web Services \(AWS\)](#)
- ? 3: [Exam Readiness: AWS Certified DevOps Engineer - Professional](#)
- ? : [IAM Roles for Amazon EC2 - AWS Identity and Access Management](#)
- ? : [Working with Instance Profiles - AWS Identity and Access Management](#)
- ? : [Launching an Instance Using a Launch Template - Amazon Elastic Compute Cloud](#)
- ? : [Temporary Security Credentials - AWS Identity and Access Management](#)

NEW QUESTION 126

A company has its AWS accounts in an organization in AWS Organizations. AWS Config is manually configured in each AWS account. The company needs to implement a solution to centrally configure AWS Config for all accounts in the organization. The solution also must record resource changes to a central account. Which combination of actions should a DevOps engineer perform to meet these requirements? (Choose two.)

- A. Configure a delegated administrator account for AWS Config
- B. Enable trusted access for AWS Config in the organization.
- C. Configure a delegated administrator account for AWS Config
- D. Create a service-linked role for AWS Config in the organization's management account.
- E. Create an AWS CloudFormation template to create an AWS Config aggregator
- F. Configure a CloudFormation stack set to deploy the template to all accounts in the organization.
- G. Create an AWS Config organization aggregator in the organization's management account
- H. Configure data collection from all AWS accounts in the organization and from all AWS Regions.
- I. Create an AWS Config organization aggregator in the delegated administrator account
- J. Configure data collection from all AWS accounts in the organization and from all AWS Regions.

Answer: AE

Explanation:

<https://aws.amazon.com/blogs/mt/org-aggregator-delegated-admin/> <https://docs.aws.amazon.com/organizations/latest/userguide/services-that-can-integrate-config.html>

NEW QUESTION 130

A company that runs many workloads on AWS has an Amazon EBS spend that has increased over time. The DevOps team notices there are many unattached EBS volumes. Although there are workloads where volumes are detached, volumes over 14 days old are stale and no longer needed. A DevOps engineer has been tasked with creating automation that deletes unattached EBS volumes that have been unattached for 14 days. Which solution will accomplish this?

- A. Configure the AWS Config ec2-volume-in-use-check managed rule with a configuration changes trigger type and an Amazon EC2 volume resource target
- B. Create a new Amazon CloudWatch Events rule scheduled to execute an AWS Lambda function in 14 days to delete the specified EBS volume.
- C. Use Amazon EC2 and Amazon Data Lifecycle Manager to configure a volume lifecycle policy
- D. Set the interval period for unattached EBS volumes to 14 days and set the retention rule to delete
- E. Set the policy target volumes as *
- F. Create an Amazon CloudWatch Events rule to execute an AWS Lambda function daily
- G. The Lambda function should find unattached EBS volumes and tag them with the current date, and delete unattached volumes that have tags with dates that are more than 14 days old.
- H. Use AWS Trusted Advisor to detect EBS volumes that have been detached for more than 14 days
- I. Execute an AWS Lambda function that creates a snapshot and then deletes the EBS volume.

Answer: C

Explanation:

The requirement is to create automation that deletes unattached EBS volumes that have been unattached for 14 days. To do this, the DevOps engineer needs to use the following steps:

? Create an Amazon CloudWatch Events rule to execute an AWS Lambda function

daily. CloudWatch Events is a service that enables event-driven architectures by delivering events from various sources to targets. Lambda is a service that lets you

run code without provisioning or managing servers. By creating a CloudWatch Events rule that executes a Lambda function daily, the DevOps engineer can schedule a recurring task to check and delete unattached EBS volumes.

? The Lambda function should find unattached EBS volumes and tag them with the

current date, and delete unattached volumes that have tags with dates that are more than 14 days old. The Lambda function can use the EC2 API to list and filter unattached EBS volumes based on their state and tags. The function can then tag each unattached volume with the current date using the create-tags command. The function can also compare the tag value with the current date and delete any unattached volume that has been tagged more than 14 days ago using the delete-volume command.

NEW QUESTION 132

A DevOps engineer is working on a data archival project that requires the migration of on-premises data to an Amazon S3 bucket. The DevOps engineer develops a script that incrementally archives on-premises data that is older than 1 month to Amazon S3. Data that is transferred to Amazon S3 is deleted from the on-premises location. The script uses the S3 PutObject operation.

During a code review the DevOps engineer notices that the script does not verify whether the data was successfully copied to Amazon S3. The DevOps engineer must update the script to ensure that data is not corrupted during transmission. The script must use MD5 checksums to verify data integrity before the on-premises data is deleted.

Which solutions for the script will meet these requirements? (Select TWO.)

- A. Check the returned response for the Versioned Compare the returned Versioned against the MD5 checksum.
- B. Include the MD5 checksum within the Content-MD5 parameter
- C. Check the operationcall's return status to find out if an error was returned.
- D. Include the checksum digest within the tagging parameter as a URL query parameter.
- E. Check the returned response for the ETag
- F. Compare the returned ETag against the MD5 checksum.
- G. Include the checksum digest within the Metadata parameter as a name-value pair After upload use the S3 HeadObject operation to retrieve metadata from the object.

Answer: BD

Explanation:

<https://docs.aws.amazon.com/AmazonS3/latest/userguide/checking-object-integrity.html>

NEW QUESTION 135

A company runs its container workloads in AWS App Runner. A DevOps engineer manages the company's container repository in Amazon Elastic Container Registry (Amazon ECR).

The DevOps engineer must implement a solution that continuously monitors the container repository. The solution must create a new container image when the solution detects an operating system vulnerability or language package vulnerability. Which solution will meet these requirements?

- A. Use EC2 Image Builder to create a container image pipeline
- B. Use Amazon ECR as the target repository
- C. Turn on enhanced scanning on the ECR repository
- D. Create an Amazon EventBridge rule to capture an Inspector2 finding even
- E. Use the event to invoke the image pipeline
- F. Re-upload the container to the repository.
- G. Use EC2 Image Builder to create a container image pipeline
- H. Use Amazon ECR as the target repository
- I. Enable Amazon GuardDuty Malware Protection on the container workload
- J. Create an Amazon EventBridge rule to capture a GuardDuty finding even
- K. Use the event to invoke the image pipeline.
- L. Create an AWS CodeBuild project to create a container image
- M. Use Amazon ECR as the target repository
- N. Turn on basic scanning on the repository
- O. Create an Amazon EventBridge rule to capture an ECR image action even
- P. Use the event to invoke the CodeBuild project
- Q. Re-upload the container to the repository.
- R. Create an AWS CodeBuild project to create a container image
- S. Use Amazon ECR as the target repository
- T. Configure AWS Systems Manager Compliance to scan all managed nodes
- . Create an Amazon EventBridge rule to capture a configuration compliance state change even
- . Use the event to invoke the CodeBuild project.

Answer: A

Explanation:

The solution that meets the requirements is to use EC2 Image Builder to create a container image pipeline, use Amazon ECR as the target repository, turn on enhanced scanning on the ECR repository, create an Amazon EventBridge rule to capture an Inspector2 finding event, and use the event to invoke the image pipeline. Re-upload the container to the repository.

This solution will continuously monitor the container repository for vulnerabilities using enhanced scanning, which is a feature of Amazon ECR that provides detailed information and guidance on how to fix security issues found in your container images. Enhanced scanning uses Inspector2, a security assessment service that integrates with Amazon ECR and generates findings for any vulnerabilities detected in your images. You can use Amazon EventBridge to create a rule that triggers an action when an Inspector2 finding event occurs. The action can be to invoke an EC2 Image Builder pipeline, which is a service that automates the creation of container images. The pipeline can use the latest patches and updates to build a new container image and upload it to the same ECR repository, replacing the vulnerable image.

The other options are not correct because they do not meet all the requirements or use services that are not relevant for the scenario.

Option B is not correct because it uses Amazon GuardDuty Malware Protection, which is a feature of GuardDuty that detects malicious activity and unauthorized behavior on your AWS accounts and resources. GuardDuty does not scan container images for vulnerabilities, nor does it integrate with Amazon ECR or EC2 Image Builder.

Option C is not correct because it uses basic scanning on the ECR repository, which only provides a summary of the vulnerabilities found in your container images. Basic scanning does not use Inspector2 or generate findings that can be captured by Amazon EventBridge. Moreover, basic scanning does not provide guidance on how to fix the vulnerabilities.

Option D is not correct because it uses AWS Systems Manager Compliance, which is a feature of Systems Manager that helps you monitor and manage the compliance status of your AWS resources based on AWS Config rules and AWS Security Hub standards. Systems Manager Compliance does not scan container images for vulnerabilities, nor does it integrate with Amazon ECR or EC2 Image Builder.

NEW QUESTION 136

.....

Thank You for Trying Our Product

We offer two products:

1st - We have Practice Tests Software with Actual Exam Questions

2nd - Questions and Answers in PDF Format

AWS-Certified-DevOps-Engineer-Professional Practice Exam Features:

- * AWS-Certified-DevOps-Engineer-Professional Questions and Answers Updated Frequently
- * AWS-Certified-DevOps-Engineer-Professional Practice Questions Verified by Expert Senior Certified Staff
- * AWS-Certified-DevOps-Engineer-Professional Most Realistic Questions that Guarantee you a Pass on Your First Try
- * AWS-Certified-DevOps-Engineer-Professional Practice Test Questions in Multiple Choice Formats and Updates for 1 Year

100% Actual & Verified — Instant Download, Please Click
[Order The AWS-Certified-DevOps-Engineer-Professional Practice Test Here](#)